

80MM Thermal Printer

(Model No.: OCPP-80M)

Specification:

Printing Method	Direct Thermal
Character Size	ANK,FontA:12*24dots,FontB:9*17dots,Simplified/Traditional Chinese :24*24 dots
Column Capacity:	576dots/line OR 512dots/line
Code Page	PC347(Standard Europe),Katakana, PC850(Multilingual),PC860(Portuguese), PC863(Canadian-French),PC865(Nordic), West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858(Latin2),IranII,Latvian,Arabic,PT151(1251)
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128
Printing Speed	260mm/sec
Input Buffer	1024K bytes
Paper Width	79.5±0.5mm
MCBF(life)	100km
Printing Command	Compatible with ESC/POS
Cash Drawer Control	DC24V/1A
Paper Thickness	0.06-0.08mm
Cutter	Manual Cutter
Roll Paper	79.5±0.5mm* φ83mm
Interface	Serial + USB + LAN
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7&8/Linux/win10
Power Supply	DC24V/2.5A
Power Adapter Input	AC 110V/220V, 50~60Hz ;output:DC 24V/2.5A
Dimension	185x140x134mm(L*W*H)
Weight	1.48kg



OCPP-80M





OCPP-80M





OCPP-80M





OCPP-80M

