

OCPP-80S 80mm Thermal Printer With Auto Cutter

(Model No.: OCPP-88S)

Features:

Desktop or wall-mounted type for option.
Supports multi 1D barcodes
200mm/s printing speed
Supports 256KB NV Logo storage and 2M big buffer memory.

Technical parameters:

Printing method: Direct thermal
Printing speed: 200mm/s
Roll width: 79.5±0.5mm
Print diameter: Φ80mm
Paper thickness: 0.06-0.08mm
Column capacity: 576dots/line512 Dots/line
Line's pacing : 3.75mm(Adjustable by commands)
Print command: Compatible with the ESC/POS command
Interface type: USB+Lan (ethernet)
Cutters life: 1million cuts
Print head life: 100 km
Input buffer : 2048Kbytes
NV Flash: 256Kbytes
Power adaptor: AC110V/240V,50~60Hz
Power supply: DC 24V/2.5A
Cash drawer supply: DC 24V/1A
Work environment: Temperature(0~45) humidity(10~80%)(Non- condense)
Work environment: Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment: Temperature(-10~60°C); Humidity(10~90%)
Character size: ANK,FontA:1.5*3.0mm/ FontB 1.1*2.1mm
Barcode: UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8/CODE39/ITF /CODE93/CODE128
Characters: PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)
Physical characteristics Weight: 1.25Kg

Pictures:



OCPP-80S





OCPP-80S





OCPP-80S



Contact:

Harold Hu
OCOM Technologies Limited
Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;
Website: www.ocominc.com, www.possolution.com.cn ;
E-mail: sales14@ocominc.com ;
Skype: [sales14@ocominc.com](https://www.skype.com/name/sales14@ocominc.com)
MSN: ocomsales14@hotmail.com ;
Whatsapp: 86.18948789890;
Wechat: 18948789890(ocomsales14);
Mobile: 86.18948789890;
QQ: 1467261417;

Tel: 0086.755.86053207-814;

Fax: 0086.755.86053207-868.