

## 80MM Thermal Printer with Auto Cutter

(Model No.: OCPP-80Y)

### Features:

1. Desktop or wall-mounted type for option.
2. Supports multi Barcode Printing
3. USB,USB+LAN,USB+RS232,URL for Optional
4. Supports 256KB NV Logo storage and 2M big buffer memory.
5. Small packaging, saving on shipping costs

### Technical parameters

Printing method:	Direct thermal
Printing speed:	160 mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mm(Adjustable by commands)
Print command:	Compatible with the ESC/POS command
Interface type:	USB, USB+LAN,USB+RS232, USB+RS232+LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V,50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0~45) humidity(10~80%)(Non- condense)
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10~60°C); Humidity(10~90%)
Character size:	ANK,FontA:1.5*3.0mm/ FontB:1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8/CODE39/ITF /CODE93/CODE128, ( QR code and PDF 417 Optional)
Characters:	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2), PC858,IranII,Latvian,Arabic,PT151(1251)
Physical characteristics	Weight: 1.25Kg