

Printing speed	USB:160mm/s , U+L 200mm/s , U+BT/U+WIFI 230mm/s
Print width	72mm
Input buffer	128kbytes
NV Flash	256kbytes
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QR CODE
Character size	ANK character, Font A: 2*24dots, 1.5(W)*3.0(H) mm Font B: 9*17dots ,1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Japanese/Korea	Support (optional)
User-defined language	Support (optional)
Media	
Paper type	Thermal roll paper
Paper width	58/80mm (optional)
Paper separator	58mm/80mm(optional)
Paper Thickness	0.06~0.08mm
Paper roll diameter	80mm Max
Physical	
Dimension	173*128*131mm
Weight	0.85kg
Package box	250*140*145mm/1.3kg
12 in 1 carton	540*300*485mm/15.6kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation







Aocom
All your files











18+ YEARS

OEM/ODM EXPERIENCES

4000+

CUSTOMERS OVER 165 COUNTRIES

15,000,000+

UNITS OF ACCUMULATED SALES

CERTIFICATES

BY ISO/CE/FCC/ROHS/BIS...



CERTIFICATE



OUR COMPANY

