

OCPP-88A Point of Sale 3 inch Thermal Head Printer

(Model No.: OCPP-88A)

Features:

1. Unique appearance with reliable mould;
2. High Printing Speed up to 300mm/second;
3. Optional auto Cutter ;
4. Cord and cordless communication for options
5. Multiple interfaces available: USB, USB+Serial, USB+ LAN, USB+ Serial+ LAN; and Wifi+USB, Bluetooth+USB+LAN
6. Sound and light alarm supported suitable for kitchen application;
7. Support multiple 1D and QR code types printing;
8. Support multi international languages;
9. SDK for Android available;
10. Reliable printer head with 100km life;
11. Compatible with EPSON ESC/POS commands.

Parameters:

Printing Method	Thermal line printing
Printing Character	576dots/line (default), 512dots/line; Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters;
Font	A: 12*24dots,1.5(W)*3.0(H)mm; B: 9*17dots,1.1(W)*2.1(H)mm Simplified/Traditional : 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code
Printing Speed	250mm/sec for a single interface ,300mm/sec for Double interface and three interfaces
Interface	USB, USB+Serial, USB+ LAN, USB+ Serial+ LAN, Wifi+USB, Bluetooth+USB+LAN
Printing Command	Compatible with EPSON ESC/POS commands
Drivers	Win9X/ Window XP /Win2000/Win2003/Win Vista/ Win 7/ Win 8/win8.1/Linux, compatible with ESPON, SDK for Android available.
Printing Width	79.5±0.5mm(print width 72mm)
Paper Diameter	83mm
Paper Thickness	0.06-0.08mm
Cutter	Auto cutter (optional)
Printing Reliability	100km
Power	DC24V/2.5A
Temperature	0-45 degree C
Contrast Humidity	10-80%
External Dimension	190*145*145(mm)
Weight	1.60kg

	P/N	Description
Ordering information	OCP-88A-U	USB port, with auto cutter
	OCP-88A-UR	USB+Serial port, with auto cutter
	OCP-88A-UL	USB+Lan port, with auto cutter
	OCP-88A-URL	USB+Serial+Lan port, with auto cutter
	OCP-88A-W	Wifi+USB port, with auto cutter
	OCP-88A-BUL	Bluetooth+USB+LAN, with auto-cutter
	OCP-88A-U0	USB port, without auto cutter
	OCP-88A-UR0	USB+Serial port, without auto cutter
	OCP-88A-UL0	USB+Lan port, without auto cutter
	OCP-88A-URL0	USB+Serial+Lan port, without auto cutter
	OCP-88A-W0	Wifi+USB port, without auto cutter
	OCP-88A-BUL0	Bluetooth+USB+LAN, without auto-cutter