

# 58mm Mini Portable Bluetooth Thermal Printer

(M/N:OCPM-M06)

## Features:

1. Mini size suitable for portable application
2. Windows, Java, Linux, Android (or Android +IOS ) operation system supported
3. Bluetooth, USB and RS232 communication supported
4. SDK for Android available
5. One printer can connect up to 8 smart devices (7 Android, one Apple device) via bluetooth
6. Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby
7. Powered by rechargeable battery, power adapter, or car charger (specified models)
8. Higher print speed 90mm/sec
9. 50km thermal printer head life
10. Multiple languages supported
11. ESC/POS command set compatible

## Specification

|                      |   |
|----------------------|---|
| Model                | OCPM-M06  |
| Name                 | 58mm mini portable bluetooth thermal printer  |
| Color                | Black   |
| Interface            | USB, RS-232, Bluetooth (optional)   |
| Battery              | 7.4V DC/ 1500mAh rechargeable li-ion battery  |
| Power adaptor        | DC 9v/1.5-2A  |
| Standby time         | 4-5days after fully charged   |
| Buffer               | Input buffer:Up to 20K,Flash:256K   |
| Other function       | Paper detection, Power detection, Manual shut down, 1D&QR Code Print                              |
| Device name          | Can be customized   |
| TPH life             | 50KM  |
| Password             | Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals |
| Accessories          | Data cable, power adaptor, power cord, paper roller, CD, manual                                   |
| Power plug dimension | 3.5*1.1mm   |
| OS supporting        | Windows & Android & IOS Systems   |
| Safety standards     | CE ,FCC,Rohs etc  |
| Printing method      | Direct thermal line   |
| Resolution           | 203DPI (8dot/mm)  |
| Printing speed       | 70mm/sec (Max 90mm/sec)   |
| Print width          | 48mm  |
| Continuous printing  | 120 pieces Thermal Roll for fully charged battery   |
| Characters per Line  | Font A:32 character /Line<br>Simple, traditional Chinese:16 character /Line                       |
| Printing Command     | Compatible with ESC/POS   |
| Character size       | FontA: 12*24dots, 1.5(W)*3.0(H)<br>Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm             |

|                               |  |
|-------------------------------|--|
| Character set                 | Alphanumeric/ Chinese Kanji                            |
| <b>Media</b>                  |  |
| Paper type                    | Thermal roll paper                                     |
| Paper width                   | 57.5±0.5mm   |
| Paper feeding method          | Easy paper loading                                     |
| Paper roll diameter           | 40mm Max   |
| Paper thickness               | 0.06-0.08mm  |
| <b>Physical</b>               |  |
| Dimension                     | 105*75*45mm  |
| Weight                        | Net:360g Gross:440g                                    |
| Package box                   | 190*120*70 mm  |
| 40 in 1 carton                | 380*475*340mm/18.36kg                                  |
| <b>Environment</b>            |  |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation    |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |







ocom  
All your data

MODE POWER FEED

OCPP-M06  
58MM Portable Thermal Printer

COM

USB



>>>Self test<<<  
58-II Thermal Printer



Version : MN-C-Z02-AA  
Revised date: 24-Jul-2015  
Command standard: EPSON(ESC/POS)  
Print mode: Normal mode  
Hex mode  
Print method: Line thermal  
Print width:

>>>Self test<<<  
58-II Thermal Printer



Version : MN-C-Z02-AA  
Revised date: 24-Jul-2015  
Command standard: EPSON(ESC/POS)  
Print mode: Normal mode  
Hex mode  
Print method: Line thermal  
Print width:



OCPP-M06  
58MM Portable Thermal Printer

MODE POWER FEED

>>>Comp test<<<

Bluetooth Name:\*\*\*N0\*\*  
012345678901



华网网络打印机  
是一款便携式的  
热敏打印机，可  
用于打印各种票  
据、单据、标签  
等。它具有体积小  
、重量轻、携带方  
便、操作简单、打  
印速度快等特点。  
此外，它还支持  
蓝牙、USB、Wi-Fi  
等多种连接方式，  
使用非常方便。

Version : MN-C-Z02-AA  
Revised date: 24-Jul-2015  
Command standard: EPSON(ESC/POS)  
Print mode: Normal mode  
Hex mode  
Print method: Line thermal  
Print width:



58-II Thermal Printer

>>>Self test<<<



