2inch OCOM Handheld Bluetooth 58mm Mini Portable Thermal Receipt Printer

(Model Number: OCPP- M07)

Features:

n Mini size suitable for portable application;

n Windows, Java, Linux, Android ,IOS operation system supported;

n Bluetooth, USB and RS232 communication supported;

n SDK for Android, IOS and WIN CE available;

n 1D, 2D barcode (QR code), and image printing supported;

n Can change the printer name, password, baud rate online;

n 57*50 paper warehouse

 ${\rm n}$ One printer can connected with up to 8 smart devices (7 Android,one Apple device) visa blue tooth;

n Low powerconsumption and large capacity Lithium battery (1500mAh), 4~5 daysstandby;

n Powered by rechargeablebattery, power adapter, or carcharger (specified models)

n Higher print speed 90mm/sec;

n 100km thermal printer head life;

n Multiple languages supported;

 $n \: \mbox{ESC/POS}$ command set compatible;

Specification:

Overall Dimension (W×D×H)105×75×45mmWeight134gColorBlackPrint methodThermal line printingPrint commandsESC/POS compatible command setEffective print width48mmPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%Storage conditionsTemperature:-20~70 degC, Humidity:5%[]95%	Specification.	
ColorBlackPrint methodThermal line printingPrint commandsESC/POS compatible command setEffective print width48mmPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Overall Dimension (W×D×H)	105×75×45mm
Print methodThermal line printingPrint commandsESC/POS compatible command setEffective print width48mmPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Weight	134g
Print commandsESC/POS compatible command setEffective print width48mmPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional))Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Color	Black
Effective print width48mmPrint speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Print method	Thermal line printing
Print speedUp to 90mm/secResolution8 dots/mm(203dpi)Print font12x24/ 24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Print commands	ESC/POS compatible command set
Resolution8 dots/mm(203dpi)Print font12x24/24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Effective print width	48mm
Print font12x24/24x24Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Print speed	Up to 90mm/sec
Column capacity32 columns/ 16columnsCharacter size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[90%	Resolution	8 dots/mm(203dpi)
Character size1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Print font	12x24/ 24x24
Paper dimensions58.0±0.1mm x diameter 40.0mmPaper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Column capacity	32 columns/ 16columns
Paper thickness0.06 to 0.08mmCharacter setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Character setAlphanumeric/ Chinese KanjiInterfaceUSB, RS-232[]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Paper dimensions	58.0±0.1mm x diameter 40.0mm
InterfaceUSB, RS-232[]Bluetooth (optional)Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Paper thickness	0.06 to 0.08mm
Flash256KBPower Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Character set	Alphanumeric/ Chinese Kanji
Power Adapter9V DC/2ABattery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Interface	USB, RS-232 Bluetooth (optional)
Battery Power7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Flash	256КВ
Dattery Powerpower, it can print 120-150m paperOther featuresPaper detection, manual shut downWorking conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Power Adapter	9V DC/2A
Working conditionsTemperature:-10~50 degC, Humidity:10%[]90%	Battery Power	
	Other features	Paper detection, manual shut down
Storage conditions Temperature:-20~70 degC. Humidity:5%	Working conditions	Temperature:-10~50 degC, Humidity:10%[]90%
	Storage conditions	Temperature:-20~70 degC, Humidity:5%[]95%

Device name	2	Can be customized, letter and digital for option, at max 30 ASCII characters.
Password		Enter default pairing code "1234", it can be customized or change by customer itself. At max 6 digitals.
Power plug d	limension	3.5*1.1mm
Ordering information	OCPP-M07-BB	Android, USB+COM+Bluetooth, Battery.
	OCPP-M07-BB-AI	Android+IOS, USB+COM+Bluetooth, Battery.
	OCPP-M07-B	Android, USB+COM+Bluetooth, without Battery;
	OCPP-M07-U	Mini printer, Android, USB+COM, without Battery.
	OCPP-M07-BB-AA	Android+IOS, USB+COM+Bluetooth, Battery, 7 android +1 apple devices supported

Application Area:

Comparedto the traditional thermal receipt printer, mini printer has smaller body, morereliable capability, more steady printing and portable advantages. The Miniprinter can work on a lot of locations, such as the TAXI bill printing, administrative fees receipt printing, post receipt printing, restaurantordering information printing, online payment information printing, etc. Withthe rapid popularity of smart-mobile, tablet and so on, Mini printer will bemore widely used in the near future.













OCPP-M07





Vol:7.4V/1500mAn/11.1Wh Charge up Voltage: 8.4V Standard:GB/T 18287-2000 One year warranty Model:58LYDD-ZJ

S/N:JH2018041213966969 SHENZHEN XINXIONGLI ELECTRICAL Co. LTD

ISO FC (E M