

## OCPP- M084 3 inch bluetooth thermal receipt printer portable

### Specification

Printing	
Printing method	Direct thermal
Print width	72mm
Column capacity	8dots/mm, 576dots/line
Printing speed	80mm/s
Interface	Bluetooth□USB□Serial
Printing paper	79.5±0.5mm×φ40mm
Line spacing	3.75mm (Adjustable by commands)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns
Character size	ANK□Font A□1.5×3.0mm□12×24 dots□ Font B□1.1×2.1mm□9×17 dots□ Chinese,traditional Chinese:3.0×3.0mm□24×24 dots□
Barcode Character	
Extension character sheet	PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863□Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□PC852□Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□
Barcode types	UPC-A/UPC-E/JAN13□EAN13□JAN8□EAN8□CODE39/ITF/CODABAR/CODE93/CODE128/QR/PDF417
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Power	
Power supply	Input□AC 110V/240V, 50□60Hz
Power source	Output□DC 9V-2A
Physical characteristics	
Weight	0.19KG
Dimensions	111×88×41mm(D x W x H)
Environmental Requirements	
Work environment	Temperature (0□45) humidity(10□90%)
Storage environment	Temperature(-10□60°C) humidity(10□90%)
Reliability	
Printer head life	50KM