

OCPP-M15 58mm Mini Blue-tooth Portable Thermal Receipt Printer Support USB Port Charging

(M/N:OCPP-M15)

Features:

Windows,Android ,IOS operation system supported
SDK for Android /IOS available
1D, 2D barcode (QR code/ PDF417) Supported
image printing supported
Can change the printer name, password, baud rate online
2000mAh 18650 battery package
Support USB port charge
Higher print speed 70mm/sec
50Km thermal printer head life
Multiple languages supported
ESC/POS command set compatible

Specifications:

| General | |
|-----------------------|---|
| Model | OCPP-M15 |
| Name | 58mm mini portable bluetooth thermal printer |
| Color | Black |
| Interface | USB/Bluetooth4.0 |
| Battery | 7.4V DC/ 2000mAh rechargeable li-ion battery |
| Power adaptor | DC 5v/2A |
| Standby time | 4days after fully charged |
| Buffer | Input buffer:Up to 50K,Flash:256K |
| TPH Life | 50KM |
| Password | Enter default pairing code "1234", it can be customized or change by customers, At max 6 digitals |
| Other function | Paper detection, Power detection, Manual shut down, 1D&QR Code Print; Led indicator; Big Paper Warehouse; Quick-acting USB Charging |
| Accessories | Data cable,power adaptor,paper roller,CD,manual |
| Power plug dimension | 3.5*1.1mm |
| OS supporting | Windows &Android & IOS Systems |
| Safety standards | CE ,FCC,Rohs etc |
| Printing capability | |
| Printing method | Direct thermal line |
| Resoluiton | 203DPI (8dot/mm) |
| Printing speed | 70mm/sec (Max 90mm/sec) |
| Print width | 48mm |
| Continuous printing | 120 pieces Thermal Roll for fully charged battery |
| Characters per Line | Font A:32 character /Line Simple,traditional Chinese:16 character /Line |
| Printing Command | Compatible with ESC/POS |
| Barcode and character | |

| | |
|-------------------------------|---|
| Character size | FontA: 12*24dots, 1.5(W)*3.0(H) Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm |
| Character set | Alphanumeric/ Chinese Kanji |
| Media | |
| Paper type | Thermal roll paper |
| Paper width | 57.5±0.5mm |
| Paper feeding method | Easy paper loading |
| Paper roll diameter | 40mm Max |
| Paper thickness | 0.06-0.08mm |
| Physical | |
| Dimension | 112*83*54mm |
| Weight | Net:230g Gross:450g |
| Package box | 180*122*65 mm |
| 40 in 1 carton | 372*372*500mm/19.4kg |
| Environment | |
| Working temperature& humidity | 0 to 45 degrees centigrade, 10%~80% No condensation |
| Storage temperature& humidity | -20 to 60 degrees centigrade , 10%~90% No condensation |

Product Overview:













