58mm pocket mobile phone receipt printer mini portable bluetooth thermal printer

(Model Number: OCPP- M15)

Features:

Windows,Android,IOS operation system supported;
SDK for Android /IOS available;
1D, 2D barcode (QR code), and image printing supported;
Can change the printer name, password, baud rate online;
2000mAh 18650 battery package;
Support USB port charge
Higher print speed 70mm/sec;
50km thermal printer head life;
Multiple languages supported;
ESC/POS command set compatible.

Specification:

Interfaces	USB / Bluetooth 4.0
Print Comand	ESC/POS
Print Method	Thermal Line Printing
Pirnt Speed	70mm/sec (can up to 90mm/s)
Resolution	203DPI (8dot/mm)
No. of Total Dots	384 dots/Line
Print Width	48mm
Character Size	1.5 x 3.0mm (W x H)/3.0 x 3.0mm (W x H)
Print Font	12 x 24; 24x 24
Character Set	Alphanumeric /Chinese Kanji
Data Buffer	UP to 50K bytes
Compatible OS	Window Systems ; Android & IOS Operate Systems
Paper	
Type	Roll Paper
Width	57.5± 0.5mm
Roll Diameter	φ≤40mm
Paper Thickness	0.06-0.08mm
Electrical	
Battery	7.4VDC/2000mA
Charging mode	DC 5V/2A
Standby Time	4 days after fully charged
Continuous Printing	120 pieces Thermal Roll for fully charged battery
Physical	
Dimension	112*83*54mm
Unit Weight	440g (including accessories: lithium-ion batteries, cable, test paper)
Carton Size	47x38x34cm
GW per carton	18kg (40pcs/CTN)
Color	Black
Environmental	
Temperature	Working: -10 to 50 Degrees
Humidity	Working: 10%-90%
Warantty	12 months at least
Certificates	CE& FCC ROHS ISO9001:2008
Other Features	Paper detection, Power detection, Manual shut down, 1D&QR Code Print; Led indicator; Big Paper Warehouse; Quick-acting USB Charging
Accessories	
USB Cable	1 x 1M Cable
CD Driver	1 Piece
Adapter	5V /2A
Thermal Roll	1 Piece
Manual	1 Piece

OCPP-M15

ERROR CHARGE 🔋 ⏻ FEED

OCPP-M15

饿了么外卖

店名： 湘聚酒楼（梓云店）
单号： 103032020180528 00036
下单时间： 2018-05-28 17:43

项目名称	数量/单位	金额
香辣罗非鱼	1例	128.00
香辣猪蹄	1例	69.00
凉拌木耳	1例	28.00
老家粑粑双拼	1例	68.00

ERROR CHARGE ⏻ FEED

ERROR CHARGE ⚡ ⏻ FEED

MINI Thermal Printer

Relevant documents:

*OCPP-M15 Specification