15.6 Inch Windows/Android Touch POS Terminal

(M/N:POS-1566)

Features:

- 15.6 inch BOE brand new LCD screen
- Multi-point projected capacitive touch panel
- Removable bottom plate for smaller packaging and less shipping cost
- The main screen supports large angle rotation to meet any observation angle
- Border-less screen , the front protects against direct water splashes
- Ultra-thin body makes the product more concise and stylish
- Thick and stable aluminum base
- Cable slots inside the base make the cable more tidy
- Customer display, secondary screen and MSR installation position is reserved on the shell

Specification

| Model | POS-1566-W |
|-----------------------|---|
| Name | 15.6 inch Windows touch screen POS terminal |
| Main screen | 15.6 inch touch screen monitor |
| Resolution | 1366*768, 1920*1080 for option |
| Brightness | 250cd/m ² |
| View angle | Horizon: 160; Vertical :150 |
| Touch screen | Multi-point projected G+G capacitive touch |
| Sub-display | 11.6inch display W or W/o touch function, resolution 1366*768 |
| Customer display | 2*20 VFD mounted to back cover for option |
| Performance | |
| Motherboard | Intel Core I5 4 th CPU,other CPU need to be customized |
| System Memory | 2*SO-DIMM DDR3L 1333/1600MHz 4GB , up to 16GB |
| Storage device | Msata SSD 128GB or higher, up to 512GB |
| Audio | On board Real-tech chip |
| LAN | 10//100/1000Mbs, 1*Realtek RTL8111 LAN chip |
| | built in Mini PCI-E slot,support embedded WIFI module |
| Optional WIFI&BT | 2.4G&5G WIFI ,BT 5.0 supported for option |
| Speaker | 4ohm/2w*1 |
| Operating System | Support win10 /win11 |
| Connectivity | |
| External I/O port (I5 | power button*1 |
| 4 th) | 12V DC in jack*1 |
| , | LAN:RJ-45*1 |
| | 2*USB3.0[]4*USB2.0 |
| | COM(RS232) * 1 |
| | 1*HDMI |
| | Audio out*1 1*Mic-in |

| Package | |
|---------------------|---|
| Weight | Net 3.5kg(without power adaptor and power cord) |
| Package with foam | 470*180*400mm/4.6kg |
| inside | |
| 2 in1 box | 485*365*405mm/10kg |
| Environment | |
| Operating | 0 to 40 degrees centigrade |
| temperature | |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% No condensation |
| Storage humidity | 10%~90% No condensation |
| Accessories | |
| Power adapter | 100-240V/50-60HZ 1.5Amax AC power input |
| | ,DC12V/5A output adaptor |
| Power cable | Power cable plug compatible with USA /EU / UK etc |
| | and customized available |

Superior Visuals Precision at Your Fingertips

Brand new 15.6-inch BOE original screen, guaranteed materials



Ultra-Slim Design, Aesthetic Excellence

Only 10.5mm thick, ultra-thin bezel design









Modular Design Strong Customization Capability



Silent Operation, Unwavering Stability

Fanless design, silent and dustproof



More Scientific Layout Structure

Integrated screen and motherboard design, easy to maintain



Detachable Base, Shipping Cost Savings

Detachable assembly, reducing product size and saving transportation costs



Packaging Accessories

Beautiful packaging, original accessories





APPLICATION

