

# OEM 80mm Windows CE Auto Cutter POS Direct Thermal Receipt Printer

(Model No.: OCPP-88A)

## Features:

- 1.Unique appearance with reliable mould;
- 2.High Printing Speed up to 300mm/second;
- 3.Optional auto Cutter ;
- 4.Cord and cordless communication for options
- 5.Multiple interfaces available: USB, , USB+ Serial+ LAN; and Wifi+USB, Bluetooth+USB
- 6.Sound and light alarm supported suitable for kitchen application;
- 7.Support multiple 1D and QR code types printing;
- 8.Support multi international languages;
- 9.SDK for Android and IOS available;
- 10.Reliable printer head with 100km life;
- 11.Compatible with EPSON ESC/POS commands.

## Parameters:

Printing Method	Thermal line printing
Printing Character	576dots/line (default), 512dots/line; Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters;
Font	A: 12*24dots,1.5(W)*3.0(H)mm; B: 9*17dots,1.1(W)*2.1(H)mm Simplified/Traditional : 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code
Printing Speed	250mm/sec for a single and two interface ,300mm/sec for three interfaces
Interface	USB,USB+ Serial+ LAN, Wifi+USB, Bluetooth+USB
Printing Command	Compatible with EPSON ESC/POS commands
Drivers	Win9X/ Window XP /Win2000/Win2003/Win Vista/ Win 7/ Win 8/win8.1/Linux, compatible with ESPON, SDK for Android and IOS available.
Paper Width	79.5±0.5mm( print width 72mm)
Paper Diameter	83mm

Paper Thickness	0.06-0.08mm	
Cutter	Auto cutter (optional)	
Printing Reliability	100km	
Power	DC24V/2.5A	
Temperature	0-45 degree C	
Contrast Humidity	10-80%	
External Dimension	190*145*145(mm)	
Weight	1.60kg	
Ordering information	P/N	Description
	OCP-88A-U	USB port, with auto cutter
	OCP-88A-URL	USB+Serial+Lan port, with auto cutter
	OCP-88A-W	Wifi+USB port, with auto cutter
	OCP-88A-BU	Bluetooth+USB, with auto-cutter
	OCP-88A-U0	USB port, without auto cutter
	OCP-88A-URL0	USB+Serial+Lan port, without auto cutter
	OCP-88A-W0	Wifi+USB port, without auto cutter
	OCP-88A-BU0	Bluetooth+USB, without auto-cutter



OCPP-88A





OCP-88A





OCPP-88A





OCP-88A





OCPP-88A





OCPP-88A







OCPP-88A





OCPP-88A

