

(POS-1508)Pos Android System All in One Touch Screen Tablet Pc Supermarket Good Partner Thin Terminal Pos

(M / N: POS-1508)

OCOM Wide-screen POS terminal has stylish and ultra slim body design, It has Android and windows OS motherboard for option, it is easy to install 2nd display, MSR or VFD as modules by customers. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices

Features:

Intel Celeron series and Android board for option
Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option
Multi-point projected capacitive touch panel
Optional side MSR and VFD220 customer display
True flat and water-proof/scratch-resistant surface display

Specifications:

Model	POS-1508-W	POS-1508-A
Name	15.8 inch Windows touch screen pos terminal	15.8 inch Android touch screen pos terminal
Housing	ABS plastic and metal combined	
Color	Whole white color machine body usually	
Display		
Main screen size	15.8 inch touch screen monitor	
Resolution	1920*1080	
Brightness	350cd/m ²	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.8 and 15.6 inch display W/o touch function, resolution 1920*1080 resolution for option	
Performance		

Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 th generation CPU for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU
System Memory	1*SO-DIMM DDRIII slot, support 1333*/1600 4GB (default) 2GB/8GB for option	On board 2GB DDRIII, 4GB for option
Storage device	Msata SSD 64GB or higher, up to 256GB	16GB eMMC, support 32GB TF card expanded
Audio	On board Realtek ALC662 audio chip ALC5640	On board Realtek audio chip ALC5640
LAN	10/100Mbps, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module	10M/100M RTL8201F, 10M/100M/1000M RTL8211E for option
Operating System	Windows 7/8/10, Embedded, WEPOS, Linux	Android 8.1
Scanner	640*480 CMOS 1D/2D Barcode scanner	
Speaker	4 Ohm 3W speaker	
Printer	58/80 mm thermal printer with auto cutter	
Connectivity		
External I/O port (J1900 and RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB *5	
	N/A	TF card*1 □ SIM card*1 for option)
	RJ11 for Cash drawer *1	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC power input, DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	

More images of the products shown:









