(POS-1508)Pos Machine Computer Touch Screen Android Metal Cash Register for Bubble Tea Store

(M / N: POS-1508)

OCOM Wide-screen POS terminal has stylish and ultra slim body desgin, It has Android and windows OS motherboard for option, it is easy to install 2nd display, MSR or VFD as moudules by customers. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices

Features:

Intel Celeron series and Android board for option
Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option
Multi-point projected capacitive touch panel
Optional side MSR and VFD220 customer display
Ture flat and water-proof/scratch-resistant surface display

Specifications:

Model	POS-1508-W	POS-1508-A	
Name	15.8 inch Windows touch	15.8 inch Android touch	
	screen pos terminal	screen pos terminal	
Housing	ABS plastic and metal combined		
Color	Whole white color machine body usually		
Display			
Main screen size	15.8 inch touch screen monitor		
Resoluiton	1920*1080		
Brightness	2		
	350cd/m		
View angle	Horizon: 160; Vertical :150		
Touch screen	Multi-point projected G+G capacitive touch		
Sub-display	15.8 and 15.6 inch display W/o touch function,		
	resolution1920*1080 resolution for option		
Performance			

Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or th intel core I3 / I5 4 generation CPU for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU	
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option	On board 2GB DDRIII,4GB for option	
Storage device	Msata SSD 64GB or higer, up to 256GB	16GB eMMC, support 32GB TF card expanded	
Audio	On board Real Tek ALC662 audio chip ALC5640	On board Real Tek audio chip ALC5640	
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option	
Operating System	Windows7/8/10, Embedded,WEPOS,Linux	Android 8.1	
Scanner	640*480 CMOS 1D/2D Barcode scanner		
Speaker	4 Ohm 3W speaker		
Printer	58/80 mm thermal printer with auto cutter		
Connectivity			
External I/O port(J1900	power button*1		
and RK3288)	12V DC in jack*1 LAN:RJ-45*1		
	USB *5	TE county 1 DCIM county 1 for	
	N/A	TF card*1∏SIM card*1 for option)	
	RJ11 for Cash drawer *1	option,	
Environment			
Operating temperature	0 to 40 degrees centigrade		
Storage temperature	-10 to 60 degrees centigrade		
Working humidity	10%~80% No condensation		
Storage humidity	10%~90% No condensation		
Accessories			
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor		
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available		
CD driver	Motherboard driver and touch driver inside		
Other	500 OL		
Compliance	FCC Class A/CE Mark/LVD/C	FCC Class A/CE Mark/LVD/CCC	

More images of the products shown:













