

15.8 Inch Andorid/Windows All-In-One Self-service POS System

(M/N:POS-1508-W/A)

OCOM Wide-screen POS terminal has stylish and ultra slim body desgin,It has Android and windows OS motherboard for option,it is easy to install 2nd display,MSR or VFD as moudules by customers.This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices

Features:



Intel Celeron series and Android board for option;

Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option;

Multi-point projected capacitive touch panel;

Ture flat and water-proof/scratch-resistant surface display.

Specification

Model	POS-1508-W	POS-1508-A
Name	15.8 inch Windows touch screen pos terminal	15.8 inch Android touch screen pos terminal
Housing	ABS plastic and metal combined	
Color	Whole white color machine body usually	
Display		

Main screen size	15.8 inch touch screen monitor	
Resolution	1920*1080 IPS panel	
Brightness	220-250cd/m2	
View angle	Horizon: 178; Vertical :178	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.8 and 15.6 inch display W/o touch function, resolution1920*1080 resolution for option	
Performance		
Motherboard	Intel Celeron J6412, 2.0GHz or intel core I3 / I5 4th CPU for option	ARM Cortex-A17 -RK 3568 quad core 2.0GHz CPU
System Memory	1*SO-DIMM DDR4 slot, support 2400 mHz,4GB (default) 8GB for option	On board 2GB DDR4, 4GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB	16GB eMMC, support 32GB TF card expanded
Audio	On board Real Tek ALC662 audio chip ALC5640	On board audio chip
LAN	10/100Mbps, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module	10M/100M RTL8201F, 10M/100M/1000M RTL8211E for option
Operating System	Windows10/11	Android 11
Scanner	640*480 CMOS 1D/2D Barcode scanner	
Speaker	4 Ohm 3W speaker	
Printer	58/80 mm thermal printer with auto cutter	
Connectivity		
External I/O port(J6412 and RK3568)	Power button*1	
	12V DC in jack*1	
	LAN: RJ-45*1	
	USB *5	
	N/A	TF card slot*1, SIM card slot* 1 function need to be customized
RJ11 for Cash drawer *1		
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC power input, DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	



POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





POS-1508





Relevant documents:
[POS-1508 80driver](#)