

OCOM 1509 POS machine is a widescreen pos solution, it has a sleek and compact body with small footprint ,this model provides quick access to I/O interfaces and storage. Alumium alloy stand make the machine very stable.

Features:

Bezel-free true-flat display with PCAP touch

Spill and dust Resistant

Multiple I/O Interfaces for peripherals

Suitable for restaurants or retail stores with tough operating environments

Specification:

Model	POS-1509
Name	15.6 inch touch POS terminal
Housing	ABS plastic shell and aluminium alloy base
Color	whole black
Main screen	15.6 inch touch screen monitor
Resoluiton	1366*768
Brightness	300cd/m ²
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Performance	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually,Pentium quad-core 1.6GHz 3710 Highest Turbo Frequency2.64GHz for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs,Realtek RTL8111F Lan chip
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	
External I/O port(J1900)	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	HDMI*1
	USB3.0*1,USB2.0 *3
	COM(RS232) *1
	VGA(15Pin D-sub)*1
	Audio out*1,MIC in*1
Options	
MSR	optional side MSR
Package	
Weight	Net 4.2Kg Gross 5.6Kg
Package with foam inside	470*280*430mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation

Storage humidity	10%~90% No condensation
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC











