

□□□□POS- 1513W&POS-1513A□

□ □ □



Intel Celeron / Intel Core I3 I5 /
Rockchip RK3288 /
EMMC 8GB/16GB/32GB /
Msata SSD 64GB / SSD 128GB / 256 GB /
MSR / VFD220 /

111

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

	POS-1513W	POS-1513A
	15.1 POS	
	15.1	
	1024*768	
	250cd/	
	160 150	
	GG	
	9.7	
	2*20 VFD	
	Intel Celeron J4125, 2.0GHz intel core I3 / I5 4th CPU	RockchipRK35682.0GRK3288
	1*SO-DIMM DDR42400mHZ4GB /8GB	DDR4 2GB4GB
	Msata SSD 64GB 256GB	8GB16GB32GB EMMC
	Real Tek ALC662	Real Tek ALC5640
	10/100MbsRealtek RTL8111F Mini PCI-EWIFI	10/100MbsRealtek RTL8111F LAN Wi-Fi 802.11b/g/nBT3.0/BT4.0
	Windows10/11	8.1
I/O	*1	
	12V DC *1	
	RJ-45*1	
	USB*4	
I/O J4125	15PIN D-sub VGA *1	
	HDMI*1 RS 232*1	
	*1*1	
I/O RK3568	*1	
	TF*1	
	RJ11 *1	
	RS 232*1	
MSR	MSR	

重量	0~40kg
湿度	-10~60%
湿度	10%~80% RH
湿度	10%~90% RH
色	
重量	5.5Kg~7.0Kg
外形寸法 （mm）	440*290*425
色	
電源 仕様	110-240V/50-60HZ、DC12V/5A
電源	ACアダプタ/USB/電源ケーブル
色	
認証	FCC A /CE /LVD/CCC





















