15-inch Touch POS terminal With Aluminum Base

(Model: POS-1513W&POS-1513A)

Features:

Intel Celeron series and intel core I3 I5 processor for option;
Rockchip high speed RK3288 processor for option;
EMMC 8GB/16GB/32GB for option;
Hard Driver Msata SSD 64GB, SSD 128GB an 256 GB for option;
Multi-point projected capacitive touch panel;
Optional side MSR and VFD220 customer display mounted to back cover;
Ture flat and water-proof scratch-resistant surface display.

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

Parameter

Model	POS-1513W	POS-1513A
Name	15.1 inch aluminium alloy touch POS terminal	
Housing	aluminium alloy shell machine body and base	
Color	whole black color machine	
Display		
Main screen	15.1 inch touch screen monitor	
Resolution	1024*768	
Brightness	250cd/m2	
View angle	Horizon: 160; Vertical: 150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	9.7 inch display W/o touch function	
Customer display	2*20 VFD display mounted to back cover for option	
Performance		
Motherboard	Intel Celeron J4125, 2.0GHz or intel core I3 / I5 4th CPU for option	Rockchip series RK3568, quad core 2.0G, RK3288 for option
System Memory	1*SO-DIMM DDR4 slot, support2400mHZ, 4GB /8GB for option	On board DDR4 2GB, 4GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB	on board8GB, 16GB, 32GB EMMC for option
Audio	On board Real Tek ALC662	on board Real Tek ALC5640 audio chip
LAN	10/100Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module	10/100Mbs, Realtek RTL8111F Lan chip, Support Wi-Fi 802.11b/g/n, BT3.0/BT4.0 support
Operating System	Support Windows10/11	Up to Android 8.1
Connectivity		
External I/O port(J4125/RK3568)	Power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB*4	
External I/O port J4125	15PIN D-sub VGA *1	
	HDMI*1 or RS 232*1 for option	
	line out*1,MIC in*1	
External I/O port RK3568	Audio out*1	
	TF card port*1	
	RJ11 for cash drawer*1	
	RS 232*1	
Options		
MSR	Optional side MSR	
Environment		
Operating temperature	0 to 40 degrees centigrade	

Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Package	
Weight	Net 5.5Kg, Gross 7.0Kg
Package with foam inside	440*290*425mm
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC

当前账号A0001
商品
数量
单价
合计
马达加斯加冻黑虎虾 800g
1
108.00
108.00
新建西州蜜瓜 1.4kg/个
2
9.90
19.80
海南蜜瓜红心火龙果 1.5kg
1
19.90
19.90
丹马耗牛腱肉 500ml
1
56.00
56.00
新西兰甜青豆 200g
2
4.50
9.00
精选鲜百合 200g
1
6.90
6.90
秘鲁蓝莓 125g
1
19.90
19.90
清 空
共14件商品
合计:¥ 269.30
应收
¥269.30
实收
¥300.00
找零
¥30.70
扫描条码
清 空
支付宝
¥200
1
2
3
微信支付
¥100
4
5
6
银行卡
¥50
7
8
9
VIP 会员卡
¥20
0
00
.
现金
¥10
结算
挂单
充值
折扣
赠送
其他
Aocom

当前账号A0001
商品
数量
单价
合计
马达加斯加冻黑虎虾 800g
新建西州蜜瓜 1.4kg/个
海南蜜瓜红心火龙果 1.5kg
丹马耗牛腱肉 500ml
新西兰扇青豆 200g
精选鲜百合 200g
秘鲁蓝莓 125g
清 空
共14件商品
合计:¥ 269.30
应收
¥269.30
实收
¥300.00
找零
¥30.70
扫描条码
清 空
结算
挂单
充值
折扣
赠送
其他
ocom

当前账号A0001
商品
数量
单价
合计
马达加斯加冻黑虎虾 800g
108.00
108.00
新疆西州蜜瓜 1.4kg/个
9.90
19.80
海南蜜瓜红心火龙果 1.5kg
19.90
19.90
丹马耗牛腱肉 500ml
56.00
56.00
新西兰甜青豆 200g
4.50
9.00
精选鲜百合 200g
6.90
6.90
秘鲁蓝莓 125g
19.90
19.90
清 空
共14件商品
合计：¥ 269.30
应收
¥ 269.30
实收
¥ 300.00
找零
¥ 30.70
扫描条码
清 空
支付宝
¥200
微信支付
¥100
银行卡
¥50
VIP 会员卡
¥20
现金
¥10
1
2
3
4
5
6
7
8
9
0
00
.
结算
挂单
充值
折扣
赠送
其他
Aocom

POS MACHINE
Touch system