## **15.6 Inch Windows/Android Touch POS Terminal**

(M/N:POS-1516)

## **Features:**

- 1. 15.6 inch BOE brand new LCD screen
- 2. Multi-point projected capacitive touch panel
- 3. Removable bottom plate for smaller packaging and less shipping cost
- 4. The main screen supports large angle rotation to meet any observation angle
- 5. Borderless screen , the front protects against direct water splashes
- 6. Ultra-thin body makes the product more concise and stylish
- 7. Thick and stable aluminum base
- 8. Cable slots inside the base make the cable more tidy
- 9. Customer display, secondary screen and MSR installation position is reserved on the shell

## **Specification**

Model	POS-1516-W	POS-1516-A	
Name	15.6 inch Windows touch	15.6 inch Android touch screen pos terminal	
	screen pos terminal		
Housing		ABS plastic machine body with aluminium alloy base	
Color	whole black color machine b	whole black color machine body	
Main screen	15.6 inch touch screen monitor		
Resoluiton	1366*768, 1920*1080 for option		
Brightness	2 300cd/m		
View angle	Horizon: 160; Vertical :150		
Touch screen	Multi-point projected G+G capacitive touch		
Sub-display	15.6inch display W or W/o touch function, resolution 1366*768 or 1920*1080 resolution for option		
Customer display	2*20 VFD or 2*20 LCD mounted to back cover for option		
Performance			
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or th intel core I3 / I5 4 generation CPU for option	RK3566, quad core 1.8GHz CPU	
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option	On board 2GB DDRIII,4GB for option	
Storage device	Msata SSD 64GB or higer, up to 256GB	32GB eMMC,	
Audio	On board Real Tek ALC662 audio chip ALC5640	On board Real Tek audio chip ALC5640	
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option	
Operating System	W i n d o w s 7 / 8 / 1 0 , Embedded,WEPOS,Linux	Android 11	
Connectivity			
connectivity			

External I/O port(J1900 and RK3288)	12V DC in jack*1 LAN:RJ-45*1 USB *4	
	COM(RS232) * 1	COM(RS232) * 2
	VGA(15Pin D-sub)*1	RJ11 for Cash drawer *1
	Audio out*1	MIC in*1 ,Audio out*1
Packge		
Weight	Net 4.0 Kg Gross 5.0 Kg	
Package with foam	460*185*420 mm for single screen	
inside		
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	























