

15.1 Inch All In One Touch POS Terminal

(M/N:POS-1519)

OCOM 1519 series POS terminal has aluminium alloy base, It has intel Celeron and intel core I series CPU for option, it is easy to access IO port for external devices such as thermal printer, label printer, mobile USB disk. This model is very convenient for maintenance by removing the back cover

Features:

- l. Intel Celeron series and intel core I3 I5 processor for option
- m. Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option
- n. Multi-point projected capacitive touch panel
- o. Optional side MSR and VFD220 customer display mounted to back cover
- p. True flat and water-proof scratch-resistant surface display
- q. Save shipping cost by dismounting the base plate to shrink the package if needed

Specification

| | |
|--------------------------|--|
| Model | POS-1519 |
| Name | 15.1 inch all in one touch POS terminal |
| Housing | Plastic shell machine body and aluminium base |
| Color | whole black color machine |
| Display | |
| Main screen | 15.1 inch touch screen monitor |
| Resolution | 1024*768 |
| Brightness | 250cd/m ² |
| View angle | Horizon: 150; Vertical :140 |
| Touch screen | Multi-point projected G+G capacitive touch |
| Sub-display | 15.1 inch display or 12.1inch display W/o touch function for option |
| Customer display | 2*20 VFD or 2*20 LCD display mounted to back cover for option |
| Performance | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz, or Intel Celeron J4125,intel core I3 / I5 CPU for option |
| System Memory | 1*SO-DIMM DDRIII slot, 4GB DDR3L/1333, 8GB for option |
| Storage device | Msata SSD 64GB or higher, up to 256GB |
| Audio | On board Real Tek ALC662 |
| LAN | 10/100Mbps, Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module |
| Operating System | Windows7/8/10, Embedded,WEPOS,Linux |
| Connectivity | |
| External I/O port J1900 | power button*1,12V DC in Jack*1 |
| | LAN:RJ-45*1 |
| | USB*6 |
| | 15PIN D-sub VGA *1 |
| | RS 232*2 |
| | line out*1,MIC in*1 |
| Options | |
| MSR | optional side MSR |
| Package | |
| Weight | Net 6.5Kg, Gross 8.0Kg for single screen |
| Package with foam inside | 425*275*405mm for single screen, 440*295*425mm for dual screen |
| Environment | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% No condensation |
| Storage humidity | 10%~90% No condensation |

| Accessories | |
|---------------|--|
| Power adapter | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available |













**All in one
Touch POS system**





