

15.1 Inch All In One Touch POS Terminal

(M/N:POS-1519B)

OCOM 1519B series POS terminal has a stable base, It has intel Celeron CPU and intel core I series CPU for option, it is easy to access IO port for external devices such as thermal printer, label printer, mobile USB disk. This model is very convenient for maintenance just by removing the back cover

Features:

1. Intel Celeron J1900 series and intel core I3 I5 processor for option
2. Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option
3. 10-point projected capacitive touch panel
4. True flat and water-proof scratch-resistant surface display
5. Multi IO ports easily expand to more external devices
6. VFD220 or LED8 for customer display
7. Metal base make it stand stably

Specification

| | |
|--------------------------|--|
| Model | POS-1519B |
| Name | 15.1 inch all in one touch POS terminal |
| Housing | Plastic shell combined with metal |
| Color | whole black color |
| Main screen | |
| Main screen | 15.1 inch touch screen monitor |
| Resolution | 1024*768 |
| Brightness | 250cd/m ² |
| View angle | Horizon: 150; Vertical :140 |
| Touch screen | 10-point projected G+G capacitive touch |
| Performance | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz, optional : intel core 3th I3 CPU / intel core 4th I5 CPU |
| System Memory | 1*SO-DIMM DDRIII slot, 4GB DDR3 |
| Storage device | Msata SSD 128GB |
| LAN | 10/100Mbs, Realtek RTL8111F Lan chip |
| Operating System | Windows7/8/10, Embedded,WEPOS, Linux |
| Connectivity | |
| External I/O ports | power button*1, 12V DC in Jack*1 |
| | LAN:RJ-45*1 ,USB*6 |
| | 15PIN D-sub VGA *1 |
| | RS 232*2 for J1900, RS232*1,HDMI*1 for I3 I5 |
| | line out*1,MIC in*1 |
| Package | |
| Weight | Net 6.5Kg, Gross 7.5Kg |
| Package with foam inside | 410*290*445mm |
| Environment | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Accessories | |
| Power adapter | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor |
| Power cable | Power cable plug compatible with USA /EU / UK etc... |











