

15.6-inch Windows Touch Screen POS Terminal with Aluminium Alloy Base (M/N: POS-1520)

OCOM 1520 wide-screen POS terminal has aluminium alloy base, It has intel Celeron and intel core I series CPU for option, it is easy to access IO port for external devices such as thermal printer, label printer, mobile USB disk. This model is very convenient for maintenance by removing the back cover.

Features:



15.6-inch BOE brand new LCD screen;

Multi-point projected capacitive touch panel;

Borderless screen, the front protects against direct water splashes;

Thick and stable aluminium base;

Cable management make cashier desk more tidy;

Customer display, secondary screen and MSR installation position is reserved for option.

Specification

Model	POS-1520
Name	15.6 inch Windows touch screen pos terminal
Housing	ABS plastic machine body with aluminium alloy base
Color	Whole black color machine body
Display	
Main screen	15.6 inch touch screen monitor
Resoluiton	1366*768
Brightness	250cd/m ²
View angle	Horizon: 150; Vertical: 140
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	13.3 inch display, W or W/o touch function, resolution 1366*768
Customer display	2*20 VFD mounted to back cover for option
Performance	
Motherboard	Intel Celeron J4125, 2.0GHz or intel core I3 / I5 CPU for option
System Memory	1*SO-DIMM DDR4 slot, support 2400 MHZ, 4GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module
Operating System	Windows7/8/10, Embedded, WEPOS, Linux
Connectivity	

External I/O port(J4125)	Power switch*1, 12V DC in Jack*1
	LAN: RJ-45*1
	USB *6
	COM(RS232) * 1, Can be expanded more RS232 ports for option
	VGA(15Pin D-sub)*1
	Audio out*1, MIC in*1
Options	
MSR	Optional side MSR
Package	
Weight	Net: 4.0Kg, Gross: 6.0Kg
Package with foam inside	460*295*415mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	110-240V/50-60HZ AC power input, DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc



























