## 15.1-inch Android Touch Screen POS Terminal with Aluminium Alloy Base

(M/N:POS-1523)



OCOM 1523 series POS terminal with metal base, it has Intel Celeron and Intel Core I series CPU for option, it is easy to access the IO port for external devices, such as thermal printer,

label printer, mobile USB disk. This model is very convenient for maintenance by removing the back cover.

## Features:

Intel Celeron series and Intel core I3 I5 processor for option

Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option

Multi-point projected capacitive touch panel

True flat and water-proof scratch-resistant surface display

Optional side MSR and VFD220 customer display mounted to back cover

## Specification

| Model            | POS-1523  |  |  |
|------------------|---|--|--|
| Name             | 15.1 inch all in one touch POS terminal                             |  |  |
| Housing          | Plastic shell machine body and aluminium base                       |  |  |
| Color            | Whole black color machine   |  |  |
| Display          |   |  |  |
| Main screen      | 15.1 inch touch screen monitor                                      |  |  |
| Resolution       | 1024*768  |  |  |
| Brightness       | 250cd/m2  |  |  |
| View angle       | Horizon: 150; Vertical :140   |  |  |
| Touch screen     | Multi-point projected G+G capacitive touch                          |  |  |
| Sub-display      | 15.1 inch display or 12.1inch display W/o touch function for option |  |  |
| Customer display | 2*20 VFD for option   |  |  |
| Performance      |   |  |  |
| Motherboard      | Intel Celeron J4125, Intel core I3 / I5 CPU for option              |  |  |
| System Memory    | 1*SO-DIMM DDR4 slot, 4GB DDR4 RAM/8GB RAM for option                |  |  |

| Storage device             | Msata SSD 64GB or higher   |  |  |  |
|----------------------------|--|--|--|--|
| LAN                        | 10/100/1000Mbs   |  |  |  |
| Operating System           | Windows10/11   |  |  |  |
| Connectivity               |  |  |  |  |
| External<br>I/O port J4125 | Power button*1, 12V DC in Jack*1   |  |  |  |
|                            | LAN:RJ-45*1  |  |  |  |
|                            | USB2.0*4, USB3.0*2   |  |  |  |
|                            | 15PIN D-sub VGA *1   |  |  |  |
|                            | HDMI*1   |  |  |  |
|                            | Line out*1, MIC in*1   |  |  |  |
| Options                    |  |  |  |  |
| MSR                        | Optional side MSR  |  |  |  |
| Package                    |  |  |  |  |
| Weight                     | Net 6.5Kg, Gross 8.0Kg for single screen                                   |  |  |  |
| Package with foam inside   | 425*275*405mm for single screen, 420*315*475mm for dual screen             |  |  |  |
| Environment                |  |  |  |  |
| Operating temperature      | 0 to 40 degrees centigrade   |  |  |  |
| Storage temperature        | -10 to 60 degrees centigrade   |  |  |  |
| Working humidity           | 10%~80% No condensation  |  |  |  |
| Storage humidity           | 10%~90% No condensation  |  |  |  |
| Accessories                |  |  |  |  |
| Power adapter              | 110-240V/50-60HZ AC power input, DC12V/5A output adaptor                   |  |  |  |
| Power cable                | Power cable plug compatible with USA /EU / UK etc and customized available |  |  |  |