15.6-inch Windows/Android Touch POS Terminal

(M/N: POS-1566)

OCOM Wide-screen POS terminal has stylish and ultra slim body design, It has Android and windows OS motherboard for option, it is easy to install 2nd display, MSR or VFD as modules by customers. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices.

Features:



15.6 inch BOE brand new LCD screen;

Multi-point projected capacitive touch panel;

Removable bottom plate for smaller packaging and less shipping cost;

The main screen supports large angle rotation to meet any observation angle;

Border-less screen, the front protects against direct water splashes;

Ultra-thin body makes the product more concise and stylish;

Thick and stable aluminum base;

Cable slots inside the base make the cable more tidy;

Customer display, secondary screen and MSR installation position is reserved on the shell.

Specification

	15.6 inch Windows touch screen POS terminal 15.6 inch touch screen monitor
	15 6 inch tauch screen monitor
Main screen 1	13.6 men toden screen monitor
Resolution 1	1366*768, 1920*1080 for option
Brightness 2	250cd/m²
View angle	Horizon: 160; Vertical: 150
Touch screen	Multi-point projected G+G capacitive touch
INITEDIATE	11.6inch display W or W/o touch function, resolution 1366*768
Customer display	2*20 VFD mounted to back cover for option
Performance	
Motherboard I	Intel Core I5 4th CPU, other CPU need to be customized
System Memory 2	2*SO-DIMM DDR3L 1333/1600MHz 4GB, up to 16GB
Storage device	Msata SSD 128GB or higher, up to 512GB
Audio	On board Real-tech chip
H AN	10//100/1000Mbs, 1*Realtek RTL8111 LAN chip built in Mini PCI-E slot, support embedded WIFI module
Optional WIFI&BT	2.4G&5G WIFI, BT 4.0 supported for option
Speaker	4ohm/2W*1
Operating System	Support Win10 /Win11
Connectivity	
External I/O port(J4125 and RK3566)	Power button*1
	12V DC in jack*1
	LAN: RJ-45*1
	USB3.0*2□USB2.0*4
	COM(RS232) * 1
	HDMI*1
	Audio out*1∏Mic-in*1
Package	
Weight 5	5.5kg
Package with foam inside	470*170*385mm
Environment	
Operating temperature (0 to 40 degrees centigrade

Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	100-240V/50-60HZ 1.5Amax AC power input, DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available



Superior Visuals Precision at Your Fingertips

Brand new 15.6-inch BOE original screen, guaranteed materials



Ultra-Slim Design, Aesthetic Excellence

Only 10.5mm thick, ultra-thin bezel design









Modular Design Strong Customization Capability



Silent Operation, Unwavering Stability

Fanless design, silent and dustproof



More Scientific Layout Structure

Integrated screen and motherboard design, easy to maintain



Detachable Base, Shipping Cost Savings


Detachable assembly, reducing product size and saving transportation costs



Packaging Accessories

Beautiful packaging, original accessories





APPLICATION

