

15.1 Inch Auminium Alloy Shell POS Terminal

(Model No.: POS-15T02)



OCOM Square screen POS terminal has auminium alloy shell, It has intel Celeron and intel core I series CPU for option, its power adaptor could be installed inside the base which make worktable neater, it has rich I/O interfaces to be connected to more external devices.

Features:

Intel Celeron series and intel core I series motherboard for option;

Hard Driver Msata SSD 64GB, SSD 128GB an 256 GB for option;

Multi-point projected capacitive touch panel;

Optional side MSR and VFD220 customer display;

Ture flat and water-proof/scratch-resistant surface display;

Side USB ports make mobile USB disk easily access the machine.

Specification

Model	POS-15T02
-------	-----------

Name	15.1 inch auminium alloy shell POS Terminal
Housing	auminium alloy shell machine body with ABS pastic base
Color	whole black color machine usually
Display	
Main screen	15.1 inch touch screen monitor
Resoluiton	1024*768
Brightness	250cd/m ²
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option
Performance	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 th generation CPU for optional
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	
External I/O port(J1900)	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	USB3.0*1,USB2.0 *5
	COM(RS232) *2
	VGA(15Pin D-sub)*1
	Audio out*1,MIC in*1
Options	
MSR	optional side MSR
Package	package
Weight	Net 4.8Kg Gross 6.5Kg
Package with foam inside	420*260*410mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power cable	Power cable for 110-240V/50-60HZ AC power input, plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC



POS-15T02











POS-15T02





POS-15T02











POS-15T02



