(M/N:POS-1701)

Features:

- 1. 17inch high brightness LCD screen
- 2. Multi-point projected capacitive touch panel
- 3. Removable bottom plate for smaller packaging and less shipping cost
- 4. The main screen supports 300° rotation to meet any observation angle
- 5. Borderless screen , the front protects against direct water splashes
- 6. Ultra-thin body makes the product more concise and stylish
- 7. Thick and stable aluminum base
- 8. Cable slots inside the base make the cable more tidy
- 9. Customer display, secondary screen and MSR installation position is reserved on the shell

Specification

| Model | POS-1701 |
|-------------------------|---|
| Name | 17.1 inch touch POS terminal |
| Housing | Plastic shell and metal base |
| Color | Whole black or whole white coulor machine |
| Display | |
| Main screen | 17.1 inch touch screen monitor |
| Resoluiton | 1400*900 |
| Brightness | 2 200cd/m |
| View angle | Horizon: 60; Vertical :90 |
| Touch screen | Multi-point projected G+G capacitive touch |
| Customer display | 2*20 VFD or 2*20 LCD display mounted to back cover for option |
| Performance | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz usually or intel core th I3 / I5 4 generation CPU for option |
| System Memory | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option |
| Storage device | Msata SSD 64GB or higer, up to 256GB |
| Audio | On board Real Tek ALC662 |
| LAN | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module |
| MSR | optional side MSR |
| Operating System | Windows7/8/10, Embedded,WEPOS,Linux |
| Connectivity | |
| External | Power button*1 |
| I/O port J1900 or I3 I5 | 12V DC in jack*1 |
| | LAN:RJ-45*1 |
| | USB*6 |
| | 15PIN D-sub VGA *1 |
| | HDMI*1, RS 232*1 for I3/I5 |
| | RS232*2 for J1900 |
| | line out*1,MIC in*1 |

| Packge | |
|--------------------------|--|
| Weight | Net 4.5Kg Gross 5.5 Kg |
| Package with foam inside | 485*453*205 mm |
| <u>Environment</u> | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% No condensation |
| Storage humidity | 10%~90% No condensation |
| Accessories | |
| Power adapter | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available |
| Other | |
| Compliance | FCC Class A/CE Mark/LVD/CCC |



































Application



Bar



Mile Tea Store



Convenience Store



Restaurant





Library



Coffee Store



Bakery



Supermarket