## 17.1-inch Windows Touch Screen POS Terminal with Aluminium Alloy Base

(M/N:POS-1701)

## **Features:**

17-inch high brightness LCD screen;

Multi-point projected capacitive touch panel;

Removable bottom plate for smaller packaging and less shipping cost;

The main screen supports 300° rotation to meet any observation angle;

Borderless screen , the front protects against direct water splashes;

Ultra-thin body makes the product more concise and stylish;

Thick and stable aluminum base;

Cable slots inside the base make the cable more tidy;

Customer display, secondary screen and MSR installation position is reserved on the shell.

## **Specification**

Model	POS-1701
Name	17.1 inch touch POS terminal
Housing	Plastic shell and metal base
Color	Whole black or whole white coulor machine
Display	
Main screen	17.1 inch touch screen monitor
Resoluiton	1400*900
Brightness	200cd/m <sup>2</sup>
View angle	Horizon: 60; Vertical :90
Touch screen	Multi-point projected G+G capacitive touch
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option
Performance	
Motherboard	th Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 generation CPU for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbs,Realtek RTL8111F Lan chip
	built in Mini PCI-E slot,support embedded WIFI module
MSR	optional side MSR
MSR Operating System Connectivity	• • • • • • • • • • • • • • • • • • • •

External I/O port J1900 or I3 I5	Power button*1  12V DC in jack*1  LAN:RJ-45*1  USB*6  15PIN D-sub VGA *1  HDMI*1, RS 232*1 for I3/I5  RS232*2 for J1900  line out*1,MIC in*1
Packge	
Weight	Net 4.5Kg Gross 5.5 Kg
Package with foam inside	485*453*205 mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC





















