

Windows Android Supported POS Terminal with Thermal Printer

(M/N: POS-A15.6/A15.6-A)

Features:

- Intel Celeron Processor J1900 Quad core 2.0GHz CPU for Windows system
- 2.0GHz RK3288 for Android system
- 2GB RAM+8GB ROM standard (Android)
- 4GB RAM+64GB SSD standard (Windows)
- Multi-point capacitive touch screen
- Embedded 58mm or 80mm thermal printer(Optional)
- Embedded MSR, RFID reader(Optional)
- Stylish display panel

Applications:

- Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Parameter:

Model	POS-A15.6/POS-A15.6-A
Main Board①	Intel Celeron Processor J1900 Quad core 2.0GHz
Main Board②	2.0GHz RK3288 Processor
OS①	Windows7(Beta)
OS②	Android 6.0
Memory①	4GB RAM 64GB SSD
Memory②	2GB RAM 8GB ROM
Touch Screen	Multi-point capacitive touch
Screen Size	Main screen15.6 inch, Vice screen15.6 inch
Color	Black or White
Printer	58mm big gear thermal printer or 80mm thermal printer with Auto cutter (optional)
I/O port①J1900	USB*4
	RJ45*1
	RJ11*1Optional
	VGA*1
	LINE-OUT*1 MIC-IN*1
	DB9 RS232 port *1

I/O port(②RK3288)	RJ11*1 (Optional)
	TF slot *1
	RJ45*1
	USB*2
	Audio*1
	USB OTG port
Operating temperature	0°C to 40°C
Other Function (Android)	Bluetooth, WIFI
Optional items(Windows)	I3 I5 CPU, LCD VFD display, RFID, MSR cammera,3G, DB25 parallel port, DB9 RS232 port*3, other size screen
Optional items(Android)	3G/4G cammera, LCD VFD display, RFID,card reader, MSR,other size screen
Storage temperature	-20°Cto 60°C
Packing dimension	46*43*51cm
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put

Picture show:









POS-A15

