

11.6 inches Android POS Terminal with Thermal Printer

(M/N:POS-B11.6-A)

Features:

Elegant B base for pos machine.

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system

2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

2GB RAM+8GB ROM standard (Android)

2GB RAM+32GB SSD standard (Windows)

11.6 inches Multi-point capacitive touch screen

11.6 inches non-touch second screen,

Embedded 58mm or 80mm thermal printer(Optional)

Embedded MSR RFID reader(Optional)

Stylish display panel

Applications:

□ Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

□ Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

□ Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

□ Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Parameter:

Model : POS-B11.6/POS-B11.6-A

Main Board@ 2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android)

OS@ Android 5.1

Memory@ 2GB RAM 8GB ROM (Android)

Touch Screen : Multi-point capacitive touch

Screen Size : 11.6 inch,16:9

Customer Display : LCD customer display (Default),

Options: 11.6inches non-touch screen, VFD customer display, Other size Scree, or non-customer display

Color : Black or White

Printer : 58mm big gear thermal printer or 80mm thermal printer with Auto cutter (Options)

I/O port①J1900① USB*4

RJ45*1

RJ11*1①optional①

VGA*1

HDMI*1(for vice screen)

DB9 RS232 port *1,(can add 2 ports for optional)

I/O port(②A83T) RJ11*1 (Opional)

TF slot *1

RJ45*1

HDMI*1(for vice screen)

USB*2 (can add 4 ports for optional)

DB9 RS232 port*1

Audio*1

USB OTG port*1

Operating temperature 0°C to 40°C

Other Function (Android) Bluetooth, WIFI

Optional items(Android) 3G,4G camera, LCD VFD display,RFID,MSR,Other size Screen

Storage temperature -20°Cto 60°C

Packing dimension 46*43*51cm

Power adapter 110-240V/50-60HZ AC power Input, 12/24V output depending on the printer

