

# China factory made 15inch all in one touch screen android smart pos terminal (M/N:POS-C15)

## Features:

- 1 Intel Celeron Processor J1900 Quad core 2.0GHz HighConfiguration CPU for Windows system
- 1 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- 1 2GB RAM+8GB ROM standard (Android)
- 1 2GB RAM+32GB SSD standard (Windows)
- 1 5 wire resistive touch screen(default),Capacitivescreen for optional
- 1 58/80mm embedded thermal printer for optional
- 1 Magnetic member card reader for optional
- 1 VFD customer display or vice screen

## Applications:

- 1 Catering: hotel,restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 1 Retailer: Business Street,boutique, department store, cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa,night club, theme park, casino and point of sales for lottery ticket
- 1 Commercial: informationmanagement terminals for parking lot, inn, aviation, subway, station and wharf

## Pictureshow:



## Parameter

|                   |                                            |
|-------------------|--------------------------------------------|
| Model             | POS-C15                                    |
| Color             | Silver-gray or Black                       |
| CPU①              | Intel Celeron J1900 Quad core 2.0 GHZ      |
| CPU②              | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor |
| Memory①           | DDRIII 1066/1333*1 2GB (default) (Windows) |
| Memory②           | 2GB RAM 8GB ROM ①Android②                  |
| OS①               | Windows7(Beta)                             |
| OS②               | Android 5.1                                |
| Hard Driver       | SSD 32GB (default) (Windows)               |
| LCD panel Size    | 15 inch TFT LCD                            |
| Brightness        | 350cd/m2                                   |
| Resolution        | 1024*768(max)                              |
| Touch Screen      | 5 wire resistive touch screen              |
| Printer Parameter | Print Density 203dpi                       |
|                   | Printing Command ESC/POS                   |
|                   | Paper Roll Diameter 60mm                   |
|                   | Paper Width 58mm or 80mm                   |
|                   | Printing Speed 60mm/s or 150mm/s           |
|                   | MCBF(life) 50km                            |

|                         |                                                 |
|-------------------------|-------------------------------------------------|
| Other optional function | MSR/ VFD220 customer display/ vice screen       |
| View Angle              | Horizon: 150; Vertical :140                     |
|                         | 1* power button 12V DC in jack*1                |
|                         | HDMI*1                                          |
|                         | VGA(15Pin D-sub)*1                              |
| I/O port□J1900□         | LAN:RJ-45*1                                     |
|                         | USB(2.0)*4                                      |
|                         | RS232*2                                         |
|                         | MIC IN*1 Audio out*1                            |
|                         | RJ11*1 (Optional)                               |
|                         | TF slot *1                                      |
| I/O port□A83T□          | RJ45*1                                          |
|                         | HDMI for vice screen                            |
|                         | DB9 RS232 port*1□USB*2                          |
|                         | Audio*1                                         |
| Operating temperature   | 0°C to 40°C                                     |
| Storage temperature     | -20°C to 60°C                                   |
| Operating System        | Windows XP above, Embedded, WEPOS, Linux        |
| Power adapter           | 110-240V/50-60HZ AC power, Input DC12/5A output |