

# POS-G156 15.6 inch all in one pos machine touch screen windows android tablet POS with printer

(M/N:POS-G156/G151)

OCOM G series pos integrated high speed thermal printer inside, R&D team take time study and research to choose each materials carefully to ensure the machine work more stably and reliably, rich IO interface make a lot of connectivities available, fashionable appearance and easily maintain and flexibly be upgraded by customers. It is the best choice for many application sites such as restaurants, coffee shops, retail stores etc...

## Features:

Intel Celeron series and intel core I3 I5 processor for optional;

Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for optional;

58mm and 80mm high speed thermal printer built in for optional;

Multi-point projected capacitive touch panel;

Optional side MSR and VFD220 customer display mounted to back cover;

Ture flat and water-proof scratch-resistant surface display.

## Specification

|                  |   |   |
|------------------|---|---|
| Model            | POS-G156W/A   | POS-G151W/A   |
| Name             | 15.6 inch all in one touch screen pos terminal  | 15.1 inch all in one touch screen pos terminal  |
| Housing          | plastic with metal combined   |   |
| Color            | whole pearl white machine body or pearl white match gray machine body                           |   |
| Display          |   |   |
| Main screen      | 15.6 inch touch screen monitor  | 15.1 inch touch screen monitor  |
| Resolution       | 1366*768  | 1024*768  |
| Brightness       | 250cd/m2  |   |
| View angle       | Horizon: 160; Vertical :150   |   |
| Touch screen     | Multi-point projected G+G capacitive touch  |   |
| Sub-display      | 15.6inch display and 13.3 inch display W/ or W/o touch function, resolution 1366*768 for option | 15.1inch display W/ or W/o touch function, resolution 1024*768                            |
| Customer display | 2*20 VFD mounted to back cover for option   |   |
| Performance      |   |   |
| Windows J1900    | Motherboard   | Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4th generation CPU for option  |
|                  | System Memory   | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option                 |
|                  | Storage device  | Msata SSD 64GB or higer, up to 256GB  |
|                  | Audio   | On board Real Tek ALC662 audio chip   |
|                  | LAN   | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module |
|                  | Operating System  | Windows7/8/10, Embedded,WEPOS,Linux   |

|                                   |  |   |
|-----------------------------------|--|---|
| Android RK3288                    | Motherboard  | Rockchip series RK3288 ,quad core 1.8G, RK3399 for option |
|                                   | System Memory  | On board DDRIII 2GB,4GB for option                        |
|                                   | Storage device   | on board16GB EMMC,32GB for option                         |
|                                   | Audio  | on board Real Tek ALC5640 audio chip                      |
|                                   | LAN  | 10/100Mbs,Realtek RTL8111F Lan chip                       |
|                                   | WIFI&BT module   | Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support             |
|                                   | Operating System   | Android 7.1   |
| Connectivity                      |  |   |
| Windows and Android(J1900&RK3288) | power button*1   |   |
|                                   | 12V DC in jack*1   |   |
|                                   | COM(RS232) * 1   |   |
|                                   | LAN:RJ-45*1  |   |
|                                   | USB *5   |   |
|                                   | MIC in*1 , Audio out*1   |   |
| Windows ( J1900)                  | LPT *1   |   |
|                                   | VGA(15Pin D-sub)*1   |   |
|                                   | RJ11 for Cash drawer *1 (optional)   |   |
|                                   | PS/2 *1 for mouse and keyboard   |   |
| Android (RK3288)                  | on board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)   |   |
|                                   | TFcard slot*1  |   |
| Options                           |  |   |
| 80mm thermal printer              | direct thermal printing  |   |
|                                   | 150mm/s printing speed   |   |
|                                   | 79.5-/+ 0.5mm paper width and printable width 72mm   |   |
|                                   | with auto cutter function and thermal head life 100km  |   |
|                                   | USB communication  |   |
| 58mm thermal printer              | direct thermal printing  |   |
|                                   | 80mm/s printing speed  |   |
|                                   | 57.5-/+ 0.5mm paper width and printable width 48mm   |   |
|                                   | thermal head life 50km   |   |
|                                   | LPT communication  |   |
| MSR                               | optional side MSR just for 15.6inch  |   |
| Web camera                        | web camera mounted on top of the display for option  |   |
| Speaker                           | 8Ohm/5W speaker inside for option  |   |
| Package                           | package  |   |
| Weight                            | Net 6.5Kg, Gross 8.5Kg for 15.6 dual screen  |   |
| Package with foam inside          | 300*465*500mm  |   |
| Environment                       |  |   |
| Operating temperature             | 0 to 40 degrees centigrade   |   |
| Storage temperature               | -10 to 60 degrees centigrade   |   |
| Working humidity                  | 10%~80%  |   |
| Storage humidity                  | 10%~90%  |   |
| Accessories                       |  |   |
| Power adapter                     | 110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine<br>DC12V/7A out put adaptor only for W/80mm printer machine |   |
| Power cable                       | Power cable plug compatible with USA /EU / UK etc and customized available   |   |
| CD driver                         | Motherboard driver and touch driver inside for option  |   |
| Other                             |  |   |
| Compliance                        | FCC Class A/CE Mark/LVD/CCC  |   |

# All In One Touch Screen POS System

---



# Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



# Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product  
**Accessories**

# SUPPORT SYSTEMS



WINDOWS



ANDROID



LINUX

# Product Interface

## Windows interfaces J1900



DC



LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0\*1



USB 2.0\*4



PS/2



MIC-IN



LIN-OUT

## Windows interfaces i3/i5



DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0\*4



USB 3.0\*1



MIC-IN



LIN-OUT

## Android interfaces RK3288



DC



COM



LAN



RJ11(optional)\*2



USB 3.0\*1



USB 2.0\*4



TF Card



MIC-IN



LIN-OUT

# Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2\*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2\*20 VFD



# Product Color



# Product Details





# Package

