

(POS-H15)Android Pos Terminal Pos Machine Touch Screen All in One Pos System with Cash Register

(M/N:POS-H156W/A-H151W/A)



OCOM H series pos integrated high speed thermal printer and scanner module inside,it is a kind of cost-effective machine for using, different frame colors make machine more beautiful, extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance.

Features:

Intel Celeron series and intel core I3 I5 processor for option

Rockchip high speed RK3288 processor

EMMC 8GB/16GB/32GB for option

Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option

58mm and 80mm high speed thermal printer built in for option

Multi-point projected capacitive touch panel

Optional side MSR and VFD220 customer display mounted to back cover

Bar-code scanner inbuilt for option

True flat and water-proof/scratch-resistant sureface display

Specifications

| | | |
|------------------|--|--|
| Model | POS-H156 | POS-H151 |
| Name | 15.6 inch all in one touch screen pos terminal | 15.1 inch all in one touch screen pos terminal |
| Housing | plastic with metal combined | |
| Color | white machine body or black machine body match orange or blue frame colors | |
| Display | | |
| Main screen | 15.6 inch touch screen monitor | 15.1 inch touch screen monitor |
| Resolution | 1366*768 | 1024*768 |
| Brightness | 250cd/m ² | |
| View angle | Horizon: 150; Vertical :140 | |
| Touch screen | Multi-point projected G+G capacitive touch | |
| Sub-display | 15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional | 15.1 inch display W/ or W/o touch function, resolution 1024*768 |
| Customer display | 2*20 VFD mounted to back cover for option | |
| performance | | |
| Windows J1900 | Motherboard | Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 th generation CPU for option |
| | System Memory | 1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option |
| | Storage device | Msata SSD 64GB or higer, up to 256GB |
| | Audio | On board Real Tek ALC662 audio chip |
| | LAN | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module |
| | Operating System | Windows7/8/10, Embedded,WEPOS,Linux |

| | | |
|-------------------------------|---|--|
| Android RK3288 | Motherboard | Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional |
| | System Memory | On board DDRIII 2GB,4GB for option |
| | Storage device | On board 16GB EMMC,32GB for option |
| | Audio | On board Real Tek ALC5640 audio chip |
| | LAN | 10/100Mbs,Realtek RTL8111F Lan chip |
| | WIFI&BT module | Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support |
| | Operating System | Android 7.1 |
| Connectivity | | |
| Windows/Android(J1900&RK3288) | power button*1 | |
| | 12V DC in jack*1 | |
| | LAN:RJ-45*1 | |
| | USB *6 | |
| | MIC in*1, Audio out*1 | |
| Windows(J1900) | COM(RS232) *1 or HDMI*1 for option | |
| | VGA(15Pin D-sub)*1 | |
| | RJ11 for Cash drawer *1 for option | |
| Android(RK3288) | COM(RS232) *1 | |
| | On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional) | |
| | TF card slot*1 | |
| Options | | |
| 80mm thermal printer | direct thermal printing | |
| | 100mm/s printing speed | |
| | 79.5-/+ 0.5mm paper width and printable width 72mm | |
| | with auto cutter function and thermal head life 50km | |
| | LPT communication | |
| 58mm thermal printer | direct thermal printing | |
| | 85mm/s printing speed | |
| | 57.5-/+ 0.5mm paper width and printable width 48mm | |
| | thermal head life 50km | |
| | LPT communication | |
| MSR | optional side MSR | |
| Web camera | web camera mounted on top of the display for option | |
| Scanner | support 1D&2D code-scanning for option | |

| | |
|--------------------------|--|
| Speaker | 4ohm/5w speakers inside for option |
| Package | package |
| Weight | net□5.6Kg , gross:7.7Kg for 15.6 with15.6 dual screen /no printer built in |
| Package with foam inside | 340*450*480mm |
| 2in1 carton | 700*460*500mm /gross□17Kg |
| Environment | |
| Operating temperature | 0 to 40 degrees centigrade |
| Storage temperature | -10 to 60 degrees centigrade |
| Working humidity | 10%~80% |
| Storage humidity | 10%~90% |
| Accessories | |
| Power adapter | 110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A out put adaptor only for W/ 80mm printer machine |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available |
| CD driver | Motherboard driver and touch driver inside for option |
| Other | |
| Compliance | FCC Class A/CE Mark/LVD/CCC |

More product pictures shown



No need tools to remove the back cover ,much conveniently for

upgrading RAM/SSD by and serviceability by customers



Side USB ports make machine more easily uploading and downloading



external IO ports



Package

