## (POS-H15)15.6 OR 15.1 INCH ALL IN ONE TOUCH POS Terminal

(M / N: POS -H156W / A-H151W / A)



OCOM H Series pos Integrated High Speed Thermal Printer and Scanner Module Inside, IT IS A Kind of Cost-Effective Machine For Using, Different Frame Colors Make Machine More Beautiful, Extended I Interface Make a Few More External Devices Connected, Newly Designed Rear Cover Which Can Be Easily Removed Without Tools for Faster Installation and Maintenance.

## **Features:**

Intel Celeron Series and Intel Core i3 i5 Processor for option

RK3288 high speed RockChip processor

EMMC 8 GB / 16GB / 32 GB for option

MSATA SSD 64GB Hard Driver, SSD 128GB A 256 GB for option

58 mm high speed thermal printer and 80 mm integrated for option

Multi-point projected capacitive tactile panel

Optional side MSR and VFD220 display the customer's display mounted on the pos Teriore cover

Integrated bar-codes scanner for option

## **Specifications:**

Template		POS -H156	POS -H151	
First name		15.6 INCH ALL IN ONE TOUCH SCREEN pos TERMINAL	15.1 INCH ALL IN ONE TOUCH SCREEN pos TERMINAL	
Accommodation		Plastic with metal combined		
Color		White Machine Body or Black Machine Body Match Orange Or Blue Frame Colors		
Screen				
Main screen		15.6 Inch Touch Screen Monitor	15.1 inch Touch Screen Monitor	
Resolution		1366 * 768	1024 * 768.	
Brightness		250cd / m. <sup>2</sup> .		
Angle view		Horizon: 150; Vertical: 140		
Touch screen		Capacitive touch of multi-point G + G		
Under-es pos ion		Display w / or w / o Touch Function,	15.1 Inch Display w / or w / o Touch Function, Resolution 1024 * 768	
Customer display		2 * 20 VFD Mounted to I	Back Cover for Option	
performance				
Windows J1900	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or Intel Core i3 / i5 4 <sup>The th.</sup> Generation CPU for option		
	System memory	1 * SO-DIMM DDRIII Slot, Support1333 * / 1600 2GB / 4GB / 8GB FOR OPTION		
	DISA pos IVI of storage	Msata SSD 64 GB or Higer, up to 256 GB		
	Audio	ON BOARD REAL TEK ALC662 AUDIO CHIP		
	LAN	10 / 100Mbs, Realtek RTL8111F LAN Chip Mini PCI-E Slot integrated, built-in WiFi module support		
	Operating system	Windows7 / 8/10, Embed	dded, We POS, Linux	

	1		
Android RK3288	Motherboard	Rockchip Series RK3288, Quad Core 1.8G, RK3399 for optional	
INNOZOO	System	On Board Ddriii 2GB, 4GB for option	
	System memory	On Board Durin 20B, 40B for option	
	DISA pos IVI	On Board 16GB EMMC, 32GB for option	
	of storage		
	Audio	ON BOARD REAL TEK ALC5640 AUDIO CHIP	
	LAN	10 / 100Mbs, Realtek RTL8111F LAN Chip	
	WiFi & BT Module	Support Wi-Fi 802.11b / g / n, BT3.0 / BT4.0 Support	
	Operating system	Android 7.1	
Connectivity			
	/ Android	Power button * 1	
(J1900 &	RK3288)	12V DC in Jack * 1	
		LAN: RJ-45 * 1	
		USB * 6	
		MIC IN * 1, AUDIO OUT * 1	
Windows (J1900)		Com (rs232) * 1 or hdmi * 1 for option	
	•	VGA (15pin D-Sub) * 1	
		RJ11 For Cash Drawer * 1 For Option	
Android (RK3288)		COM (RS232) * 1	
		On Board RJ11 For Cash Drawer * 1, RJ11 from	
		Printer Port For Cash Drawer * 1 (Optional)	
		TF Card Slot * 1	
Options			
80mm Thermal		Direct Thermal Printing	
Printer		100mm / s Pringting Speed	
		79.5 - / + 0.5mm Paper Width and Printable Width 72mm	
		With Austo Cutter Function and Thermal Head Life 50km	
		LPT Communication	
58mm Thermal Printer		Direct Thermal Printing	
		85mm / s pringting speed	
		57.5 - / + 0.5mm Paper Width and Printable Width 48mm	
		Thermal Head Life 50km	
		LPT Communication	
		1	

MSR.	Optional side MSR.
web room	Web Room Mounted On Top of the Display For Option
Scanner	Support 1D & 2D Code-Scanning for Option
Speaker	4ohm / 5W Speakers Inside for option
Package	package
Weight	NET: 5.6kg, Gross: 7.7kg for 15.6 with15.6 Dual Screen / No Printer Built in
Pack with foam inside	340 * 450 * 480mm
2in1 carton	700 * 460 * 500mm / Gross: 17kg
Environment	
Operating	0 to 40 degrees Celsius
temperature	
Storage temperature	-10 at 60 degrees centigrade
Work humidity	10% ~ 80%
Storage humidity	10% ~ 90%
Accessories	
Power adapter	110-240V / 50-60Hz AC PowerInput, DC12 / 5A Output Adapter for w / o Printer and w / 58mm Printer Machine DC12V / 7A Out Put Adaptor Only for w / 80mm Printer Machine
Power cord	Power cord plug compatible with USA / EU / UK etc. And customized
CD Driver	Motherboard driver and touch drivers inside for the option
Other	
Conformity	FCC class A / CE / LVD / CCC class sign

More images of the products shown



No need for tools to remove the pos Temester cover, very comfortably for updating the RAM / SSD and customer maintenance  $\,$ 



The side USB ports make the machine more easily upload and unload



Doors external



## Package

