21.5 Inch Windows/Android Self-Service POS System

(M/N:POS-K003)

Features:

Top design in this kiosk industry, quick respones, run stably;

Highly intergrating multi-function, space-saving, easy to operate;

Best shopping experience and improving the store image;

Labor cost-saving;

Time saving for the customers waiting at cashier front desk;

High quality scanner make goods-scanning quickly;

Support the payment of Wechat and Alipay;

Support wall-mounting and standing alone.

Specification

| Model | POS-K003-W | S-K003-W POS-K003-A | | |
|-------------------|--|---------------------|--|--|
| Name | 21.5 inch all in one touch screen Kiosk | | | |
| Housing | plastic with metal combined | | | |
| Color | whole white color | | | |
| Display | | | | |
| Main screen size | 21.5 inch touch screen monitor | | 21.5 inch touch screen monitor | |
| Resolution | 1920*1080 1920*1080 | | 1920*1080 | |
| colorBrightness | 250cd/m2 | | | |
| View angle | Horizon: 178; Vertical :178 | | | |
| Touch screen | 10-point projected G+G capacitive touch | | | |
| Performance | | | | |
| Motherboard | Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4th generation CPU for option | AR | M Cortex-A17 -RK 3288 quad core 1.8GHz CPU | |
| System Memory | 1*SO-DIMM DDRIII slot, support1333*/1600 4GB | On | board 2GB DDRIII | |
| Storage device | Msata SSD 64GB | 16 | GB eMMC | |
| Audio | On board Real Tek ALC662 audio chip | | board Real Tek audio chip ALC5640 | |
| LAN | 10/100Mbs,Realtek RTL8111F Lan chip | 10 | M/100M,RTL8201F | |
| WIFI | Support 802.11 a/b/g | Su | pport 802.11 a/b/g | |
| Speaker | Built in 8ohm/10watt speakers | | | |
| Camera | Face recognition for payment (option) | | | |
| Operating System | Windows7/8/10, Embedded,WEPOS,Linux | Ar | ndroid 7.1 | |
| Connectivity | | | | |
| External I/O port | Power switch*1 | | | |
| (J1900/RK3288) | 100V-240V 50HZ/60HZ AC power Socket*1 | | | |
| | USB*2 | | | |
| | LAN:RJ-45*1 | | | |
| Scanning platform | package | | | |
| Light Source | Illumination:617nm red LED | | | |
| Power supply | 5V DC | | | |
| Support 1D | UPC,EAN, Code128, Code 39,Code 93, Code11, Interleaved 2 of 5, Matrix 2 of 5, Codabar, MSI Plessey,GS1 DataBar,China Postal,Korean Postal, etc | | | |
| Support 2D | PDF417,Micro PDF417,Data Matrix,Maxicode,QR Code,Micro QR,Aztec,Hanxin, etc | | | |
| Barcode precision | 4 mil code39 | | | |

| Barcode Sensitivity | Pitch:±60°@ 0°Roll and 0°Skew Roll:±360°@ 0°Pitchand0°Skew Skew:±65°@ 0°Roll and 0°Pitch | | |
|------------------------|--|--|--|
| Prompt Mode | Buzzer | | |
| Interface | USB | | |
| Printer | | | |
| 80mm thermal | Direct thermal printing | | |
| printer | 150mm/s pringting speed | | |
| | 79.5-/+ 0.5mm paper width and printable width 72mm | | |
| | Auto cutter function | | |
| | Power DC 24V | | |
| | Resoluiton 203DPI | | |
| Environment | | | |
| Operating temperature | 0 to 40 degrees centigrade | | |
| Storage temperature | -10 to 60 degrees centigrade | | |
| Working humidity | 10%~80% No condensation | | |
| Storage humidity | 10%~90% No condensation | | |
| Accessories | | | |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available | | |
| CD driver | Motherboard driver and touch driver inside (Option) | | |
| Other | | | |
| Compliance | FCC Class A/CE Mark/LVD/CCC | | |











