

# (POS-L156)Point Of Sale System Billing Pos Terminal System Windows Dual Screen Cash Register Machine Touch Pos I3

(M / N: POS-L156)

OCOM POS-L156 series pos integrated high speed thermal printer inside,stylish design, working stably and reliably,rich IO interface make a lot of connectivities available, easily maintain and flexibly be upgraded by customers.it is the best choice for many application sites such as restaurants, coffee shops,retail stores etc...

## Features:

Intel Celeron series and intel core I3 I5 processor for option  
Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option  
58mm and 80mm high speed thermal printer built in for option  
Multi-point projected capacitive touch panel  
Optional side MSR and VFD220 customer display mounted to back cover  
Ture flat and water-proof scratch-resistant surface display

## Specifications:

|                    |   |
|--------------------|---|
| Model              | POS-L156  |
| Name               | 15.6 inch all in one touch screen pos terminal  |
| Housing            | plastic with metal combined   |
| Color              | whole white machine body or whole black machine body  |
|                    |   |
| Main screen        | 15.6 inch touch screen monitor  |
| Resolution         | 1366*768  |
| Brightness         | 250cd/m <sup>2</sup>  |
| View angle         | Horizon: 160; Vertical :150   |
| Touch screen       | Multi-point projected G+G capacitive touch  |
| Sub-display        | 15.6inch display W / or W / o touch function, resolution 1366*768 for option                      |
| Customer display   | 2*20 VFD mounted to back cover for option   |
| <b>Performance</b> |   |
| Motherboard        | Intel Celeron Bay Trail J1900 2.0GHz ,or intel celeron J4125,or intel core I3 / I5 CPU for option |

|                          |  |
|--------------------------|--|
| System Memory            | 1*SO-DIMM DDRIII slot, support 4GB DDR3L / 1333MHZ(default) ,8GB for option  |
| Storage device           | Msata SSD 64GB or higer, up to 256GB   |
| Audio                    | On board Real Tek ALC662 audio chip  |
| LAN                      | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module  |
| Operating System         | Windows7 / 8 / 10, Embedded,WEPOS,Linux  |
| <b>Connectivity</b>      |  |
| External I/O port J1900  | power button*1   |
|                          | 12V DC in Jack*1   |
|                          | LAN:RJ-45*1,RJ11 for cash drawer   |
|                          | USB*6  |
|                          | 15PIN D-sub VGA *1   |
|                          | RS 232*1<br>line out*1, MIC in*1   |
| <b>Options</b>           |  |
| 80mm thermal printer     | direct thermal printing  |
|                          | 150mm/ s printing speed  |
|                          | 79.5- / + 0.5mm paper width and printable width 72mm   |
|                          | with auto cutter function and thermal head life 50km   |
| 58mm thermal printer     | direct thermal printing  |
|                          | 85mm/s printing speed  |
|                          | 57.5- / + 0.5mm paper width and printable width 48mm   |
|                          | thermal head life 50km   |
| MSR                      | optional side MSR  |
| Web camera               | web camera mounted on top of the display for option  |
| Scanner                  | support 1D&2D code-scanning for option   |
| Speaker                  | 4ohm/5w speakers inside for option   |
| <b>Package</b>           |  |
| Weight                   | Net 6.5Kg , Gross: 8.0Kg for 15.6 with 15.6 dual screen with printer built in  |
| Package with foam inside | 490*310*485mm  |
| <b>Accessories</b>       |  |
| Power adapter            | 110-240V/50-60HZ AC power input ,DC12 / 5A output adaptor for W / o printer and W / 58mm printer machine<br>DC12V / 7A out put adaptor only for W / 80mm printer machine |
| Power cable              | Power cable plug compatible with USA / EU / UK etc and customized available  |

**More images of the products shown:**



















