## (POS-L156)System Pos Machine System Printer Hardware Shop Cheap Metal Touchscreen Mini Printer Pos

(M / N: POS-L156)

OCOM POS-L156 series pos integrated high speed thermal printer inside, stylish desigin, working stablely and reliably, rich IO interface make a lot of connectivities available, easily maintain and flexibly be upgraded by customers. it is the best choice for many application sites such as retaurants, coffee shops, retail stores etc...

## **Features:**

Intel Celeron series and intel core I3 I5 processor for option
Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option
58mm and 80mm high speed thermal printer built in for option
Multi-point projected capacitive touch panel
Optional side MSR and VFD220 customer display mounted to back cover
Ture flat and water-proof scratch-resistant surface display

## **Specifications:**

Model	POS-L156
Name	15.6 inch all in one touch screen pos terminal
Housing	plastic with metal combined
Color	whole white machine body or whole black machine body
Main screen	15.6 inch touch screen monitor
Resolution	1366*768
Brightness	2 250cd/m
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	15.6inch display W/ or W/o touch function, resolution 1366*768 for option
Customer display	2*20 VFD mounted to back cover for option
Performance	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz ,or intel celeron J4125,or intel core I3 / I5 CPU for option

System Memory	1*SO-DIMM DDRIII slot, support 4GB DDR3L/1333MHZ(default) ,8GB for option
Storage device	Msata SSD 64GB or higer, up to 256GB
Audio	On board Real Tek ALC662 audio chip
LAN	10/100Mbs,Realtek RTL8111F Lan chip
	built in Mini PCI-E slot, support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	Timadis770720, Embedded71121 OS,Emax
External	power button*1
I/O port J1900	12V DC in Jack*1
,, 0 , 0	LAN:RJ-45*1,RJ11 for cash drawer
	USB*6
	15PIN D-sub VGA *1
	RS 232*1
	line out*1,MIC in*1
Options	into due 2/i ii d'ii 2
80mm thermal printer	direct thermal printing
Communication of the communi	150mm/s pringting speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with atuo cutter function and thermal head life 50km
58mm thermal printer	direct thermal printing
	85mm/s pringting speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
MSR	optional side MSR
Web camera	web camera mounted on top of the display for option
Scanner	support 1D&2D code-scanning for option
Speaker	4ohm/5w speakers inside for option
Package	
Weight	Net ☐6.5Kg , Gross:8.0Kg for 15.6 with 15.6 dual screen with
	printer built in
Package with foam inside	490*310*485mm
Accessories	
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor
	for W/o printer and W/ 58mm printer machine DC12V/7A out
	put adaptor only for W/ 80mm printer machine
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available

## More images of the products shown:

































