## **11.6 Inch Android/Windows Touch Screen POS System**

(M/N: POS-M1106)

**Features:** 



Intel Celeron series and Rockchip CPU for option;

Hard Driver Msata SSD 64GB, SSD 128GB and 256 GB for option;

58mm and 80mm high speed thermal printer built in for option;

Multi-point projected capacitive touch panel;

Optional side MSR and VFD220 customer display mounted to back cover;

NFC card reader, bar-code scanner as option;

Ture flat and water-proof scratch-resistant surface display.

## Specification

Model	POS-M1106-W		POS-M1106-A
Name	11.6inch all in one Windows touch screen pos terminal		11.6 inch all in one Android touch screen pos terminal
Housing	Plastic with metal combined		
Color	Whole gray color		
Display			
Main screen size	11.6 inch touch screen moni	tor	11.6 inch touch screen monitor
Resolution	1366*768,1920*1080 for opt	ion	1366*768,1920*1080 for option
Brightness	300cd/m2		
View angle	Horizon: 160; Vertical :150		
Touch screen	Multi-point projected G+G capacitive touch		
Customer display	2*20 VFD or 5.0-inch 800* 600 resolution non-touch display mounted to back cover for option		
Performance			
Motherboard	Intel Celeron J4125, 2.0GHz	RK 3568, Cortex-55, quad core 2.0GHz / RK 3288 quad core 1.8GHz CPU for option	
System Memory	1*SO-DIMM DDR4 slot, support2400mHZ, 4GB (default) 8GB for option	On board 2GB DDR4	
Storage device	Msata SSD 64GB or higer, up to 256GB	32GB eMMC, support 32GB TF card expanded for option	
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640	
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option	
Operating System	Windows10/11	Andr	oid 11
Connectivity			

	Power button*1			
	12V DC in jack*1			
	COM(RS232) * 1, up to 3ports			
External I/O port(J4125/RK3568)	LAN: RJ-45*1			
	RJ11 for Cash drawer *1 for	r RJ11 for Cash drawer *2 for option		
	option			
	VGA(15Pin D-sub)*1	TF card slot*1		
	USB *5	USB *5		
	MIC in*1 Audio out*1	N/A		
Options				
80mm thermal printer	Direct thermal printing			
	170mm/s pringting speed			
	79.5-/+ 0.5mm paper width and printable width 72mm			
	With atuo cutter function and thermal head life 100km			
58mm thermal printer	Direct thermal printing			
	70mm/s pringting speed			
	57.5-/+ 0.5mm paper width and printable width 48mm			
	Thermal head life 50km			
MSR	ISO7811 1/2/3 Tracks, Support Dual-swiping			
NFC	ISO14443TypeA			
Scanner	1D/2D barcode decoding			
Battery	5200mAh large capacity battery (only for Android version)			
Package				
Weight	Net: 2.4kg, Gross: 3.1kg			
Package with foam inside	400*390*190mm			
Environment				
Operating temperature	0 to 40 degrees centigrade			
Storage temperature	-10 to 60 degrees centigrade			
Working humidity	10%~80% No condensation			
Storage humidity	10%~90% No condensation			
Accessories				
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor			
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available			
CD driver	Motherboard driver and touch driver inside			
Other				
Compliance	FCC Class A/CE Mark/LVD/CCC			









Relevant documents:

POS-M1106 SDK