Android POS terminal with Thermal Printer

(M/N:POS-M1106-A)

Features:

- 1. Android 7.1 operating system
- 2. RK3368 Octa-core 1.5GHz processor
- 3. 2G RAM and 8G eMMC
- 4. 11.6 Inch High-definition color screen
- 5. Standard 1366*768 resolution, can up to 1080P
- 6. Support 58/80mm thermal printer built in
- 7. Can optional VFD LCD display MSR,RFID,1/2D Barcode Scanner

Application area

- 1. Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 2. Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- 3. Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- 4. Commercial: information management terminals for parking lot, inn, aviation, subway, station and whar

Specification

| Processor | RK3368 Octa-core 1.5GHz |
|----------------------|---|
| OS | Android 7.1 (Andriod 6.0 for optional) |
| Memory | 2G RAM+ 8G ROM |
| SD | Micro SD□Up to TF 32GB) |
| Display | 11.6 Inch High-definition color screen |
| Resolution | 1366*768, (can up to 1920*1080P) |
| Touch Screen | Ten-point capacitive touch screen |
| Printer | 58mm(no cutter) or 80mm(auto cutter) thermal printer |
| Magnetic Card Reader | ISO7811 1/2/3 Tracks, Support Dual-swiping(Optional) |
| RFID Card Reader | ISO14443TypeA, (Optional) |
| Barcode Scanner | 1D/2D barcode decoding (Optional) |
| Pole display | LCD /VFD display (Optional) |
| Wi-Fi | 802.11b/g/n |
| USB | 5*USB2.0, |
| RJ11 | 2*RJ11 |
| LAN | 1*RJ45 port,100/1000 SELF-ADAPTION |
| RS232 | 1*RS232,(can tp to 3 RS232 prot) |
| Power | DC12V,5A |
| Battery | 5200mAh (Optional, Standard product does not contain a battery) |

Working environment

Working temperature: -10 °C \sim 50 °C Storage temperature: -20 °C \sim 60 °C

Relative humidity: 10% □90%







POS-M1106-A







POS-M1106-A



