

## Windows System POS terminal with Thermal Printer

(M/N:POS-M1106-W)

### Features:

1. Windows 7 Beta System
2. J1900 Quad-core 1.99GHz processor
3. 4G RAM and 64G SSD
4. 11.6 Inch High-definition color screen
5. Standard 1366\*768 resolution,can up to 1080P
6. Support 58/80mm thermal printer built in
7. Can optional 5200 mAh large capacity battery
8. Can optional VFD LCD display MSR,RFID,1/2D Barcode Scanner

### Application area

1. Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
2. Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
3. Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
4. Commercial: information management terminals for parking lot, inn, aviation, subway, and station

### Specification

|                      |  |
|----------------------|--|
| Processor            | J1900 Quad-core 1.99GHz processor  |
| OS                   | Win 7 Beta, can optional Win 10 Beta   |
| Memory               | 4G RAM+ 64G SSD  |
| Display              | 11.6 Inch High-definition color screen   |
| Resolution           | 1366*768, (can up to 1920*1080P)   |
| Touch Screen         | Ten-point capacitive touch screen  |
| Printer              | 58mm(no cutter) or 80mm(auto cutter) thermal printer   |
| Magnetic Card Reader | ISO7811 1/2/3 Tracks, Support Dual-swiping(Optional)   |
| RFID Card Reader     | ISO14443TypeA, (Optional)  |
| Barcode Scanner      | 1D/2D barcode decoding (Optional)  |
| Pole display         | LCD /VFD display (Optional)  |
| Wi-Fi                | 802.11b/g/n  |
| USB                  | 5*USB2.0,  |
| RJ11                 | 2*RJ11   |
| LAN                  | 1*RJ45 port,100/1000 SELF-ADAPTION   |
| RS232                | 1*RS232,(can tp to 3 RS232 prot)   |
| Power                | DC12V,5A   |
| Battery              | 5200mAh (Optional, Standard product does not contain a battery)  |
| Working environment  | Working temperature: -10 °C ~ 50 °C<br>Storage temperature: -20 °C ~ 60 °C<br>Relative humidity: 10%~90% |



# POS-M1106-W





# POS-M1106-W





# POS-M1106-W





# POS-M1106-W





# POS-M1106-W

