(M/N:POS-M1162-W/POS-M1162-A)

Features:

Intel Celeron series and intel I3 I5 or RK3288 CPU for option Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option 80mm high speed thermal printer built in Multi-point projected capacitive touch panel VFD220 customer display mounted to back cover NFC card reader,bar-code scanner as option Ture flat and water-proof scratch-resistant surface display

Specification

Model	POS-M1162-W	POS-M1162-A	
Name	11.6inch all in	11.6 inch all in	
	one Windows touch screen	one Android touch screen	
	pos terminal	pos terminal	
Housing	plastic with metal combined		
Color	Black and white color	Black and white color	
Display			
Main screen size	11.6 inch IPS touch screen	11.6 inch IPS touch screen	
	monitor	monitor	
Resolution	1366*768,1920*1080 for	1366*768,1920*1080 for	
	option	option	
Brightness	2		
	300cd/m		
View angle	*	Horizon: 160; Vertical :150	
Touch screen	multi-point projected G+G capacitive touch		
Vice screen	4.3inch lcd display ,resolution 800*480 for option		
Customer display	2*20 VFD mounted to back cover for option		
Performance			
Motherboard	Intel Celeron Bay Trail	ARM Cortex-A17 -RK 3288	
	J4125 2.0GHz,intel core	quad core 1.8GHz CPU	
	I3/I5 for option		
System Memory	1*SO-DIMM DDRIV	On board 2GB DDRIII	
	slot, 2133 Mhz 2GB/4GB		
	8GB for option		
Storage device	Msata SSD 64GB or higer,	16GB eMMC,support 32GB	
	up to 256GB	TF card expanded for option	
Audio	On board Real Tek ALC662	On board Real Tek audio	
	audio chip	chip ALC5640	
LAN	10/100Mbs,Realtek	10M/100M	
	RTL8111F Lan chip	RTL8201F,10M/100M/1000M	
	built in Mini PCI-E	RTL8211E for option	
	slot,support embedded	· I	
	WIFI module		
Operating System	Windows7/8/10,		
' ' '	Embedded,WEPOS,Linux	Android 7.1 and Anroid 8.1	
	•	-	

Connectivity		
	power button*1	
	12V DC in jack*1	
External I/O		
port(J4125/RK3288)	LAN:RI-45*1	
	USB *5	
	RJ11 for Cash drawer *1	
	VGA(15Pin D-sub)*1	
	MIC in*1 Audio out*1 RJ11*1	
Options	I I I I I I I I I I I I I I I I I I I	
80mm thermal printer	direct thermal printing, support label and receipt	
domini tricimai printer	200mm/s pringting speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with atuo cutter function and thermal head life 100km	
speaker	80hm/3W speaker	
WIFI	IEEE 802.11 a/b/g/n	
comunication	3G/4G	
NFC card reader	ISO14443TypeA	
scanner	1D/2D barcode decoding	
	5.0MP/Auto focus,support 1D/2D	
Camera	• •	
Battery	6000mAh large capacity battery	
Package	Not 2 1/g Cross 2 9/g	
Weight	Net 3.1Kg Gross 3.8Kg	
Package with foam inside	180*370*380mm	
2 in 1 carton	370*365*392/12kg	
Environment		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
Accessories		
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/7A output	
	adaptor	
Power cable	Power cable plug compatible with USA /EU / UK etc and	
	customized available	
CD driver	Motherboard driver and touch driver inside	
Other		
Compliance	FCC Class A/CE Mark/LVD/CCC	















































