

POS-M1162A/W 11.6 inch Android /Windows POS terminal With 80MM Thermal Receipt/Label
Printer For Options

(M/N:POS-M1162-W/POS-M1162-A)

Features:

Intel Celeron series and intel I3 I5 or RK3288 CPU for option
Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option
80mm high speed thermal printer built in
Multi-point projected capacitive touch panel
VFD220 customer display mounted to back cover
NFC card reader,bar-code scanner as option
Ture flat and water-proof scratch-resistant surface display

Specification

| Model | POS-M1162-W | POS-M1162-A |
|--------------------|---|--|
| Name | 11.6inch all in one Windows touch screen pos terminal | 11.6 inch all in one Android touch screen pos terminal |
| Housing | plastic with metal combined | |
| Color | Black and white color | |
| Display | | |
| Main screen size | 11.6 inch IPS touch screen monitor | 11.6 inch IPS touch screen monitor |
| Resolution | 1366*768,1920*1080 for option | 1366*768,1920*1080 for option |
| Brightness | 300cd/m ² | |
| View angle | Horizon: 160; Vertical :150 | |
| Touch screen | multi-point projected G+G capacitive touch | |
| Vice screen | 4.3inch lcd display ,resolution 800*480 for option | |
| Customer display | 2*20 VFD mounted to back cover for option | |
| Performance | | |
| Motherboard | Intel Celeron Bay Trail J4125 2.0GHz,intel core I3/I5 for option | ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU |
| System Memory | 1*SO-DIMM DDRIV slot, 2133 Mhz 2GB/4GB 8GB for option | On board 2GB DDRIII |
| Storage device | Msata SSD 64GB or higer, up to 256GB | 16GB eMMC,support 32GB TF card expanded for option |
| Audio | On board Real Tek ALC662 audio chip | On board Real Tek audio chip ALC5640 |
| LAN | 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module | 10M/100M RTL8201F,10M/100M/1000M RTL8211E for option |
| Operating System | Windows7/8/10, Embedded,WEPOS,Linux | Android 7.1 and Anroid 8.1 |

| Connectivity | | |
|---------------------------------|--|---------------------------|
| External I/O port(J4125/RK3288) | power button*1 | |
| | 12V DC in jack*1 | |
| | COM(RS232) * 1 | |
| | LAN:RJ-45*1 | |
| | USB *5 | |
| | RJ11 for Cash drawer *1 | |
| | VGA(15Pin D-sub)*1 | TF card slot*1,SIM slot*1 |
| | MIC in*1 Audio out*1 | RJ11*1 |
| Options | | |
| 80mm thermal printer | direct thermal printing,support label and receipt | |
| | 200mm/s printing speed | |
| | 79.5-/+ 0.5mm paper width and printable width 72mm | |
| | with auto cutter function and thermal head life 100km | |
| speaker | 8ohm/3W speaker | |
| WIFI | IEEE 802.11 a/b/g/n | |
| communication | 3G/4G | |
| NFC card reader | ISO14443TypeA | |
| scanner | 1D/2D barcode decoding | |
| camera | 5.0MP/Auto focus,support 1D/2D | |
| Battery | 6000mAh large capacity battery | |
| Package | | |
| Weight | Net 3.1Kg Gross 3.8Kg | |
| Package with foam inside | 180*370*380mm | |
| 2 in 1 carton | 370*365*392/12kg | |
| Environment | | |
| Operating temperature | 0 to 40 degrees centigrade | |
| Storage temperature | -10 to 60 degrees centigrade | |
| Working humidity | 10%~80% No condensation | |
| Storage humidity | 10%~90% No condensation | |
| Accessories | | |
| Power adapter | 110-240V/50-60HZ AC powerinput ,DC12/7A output adaptor | |
| Power cable | Power cable plug compatible with USA /EU / UK etc and customized available | |
| CD driver | Motherboard driver and touch driver inside | |
| Other | | |
| Compliance | FCC Class A/CE Mark/LVD/CCC | |





















11.6 inch Touch Screen Computer System
Model: POS-M1162
Configuration: I3800+GEMM+MSTW+1TC+Display
8200 Printer+2D Scanner
Power Input: DC 12V/1A
1909M11622118200001
Made in China



11.6 inch Touch Screen Computer System
Model: POS-M1162
Configuration: i1900+GBRAM+4SSD+NFC+Display
80MM Printer+2D Scanner
Power Input: DC 12V 7A
Barcode: POSM1162213820001
Made in China
CE FC

