

# 10.1 Inch Windows or Android Price Checker

(M/N:OCPC-001-W/OCPC-001-A)

OCOM 001 price checker has fashionable and elegant appearance,it can be installed Windows or Android OS for choosing,easy operation for the customers price checking before buying.tablet like touch screen can be mounted to wall or any other VESA standard brackets.

## Features:

1. Intel Celeron series
2. Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for optionn
3. Ture flat and water-proof scratch-resistant surface display

## Specification

Model	OCPC-001-W	OCPC-001-A
Name	10.1 inch all in one touch screen machine	10.1 inch all in one touch screen machine
Housing	plastic with metal combined	
Color	wholeblack machine body	
<b>Display</b>		
Main screen size	10.1 inch touch screen monitor	10.1 inch touch screen monitor
Resolution	1280*800	1280*800
Brightness	250cd/m <sup>2</sup>	
View angle	Horizon: 160; Vertical :150	
Touch screen	multi-point projected G+G capacitive touch	
<b>Performance</b>		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz	Rockchip series RK3288 ,quad core 1.8G,A63 CPU for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB	On board 2GB DDRIII
Storage device	Msata SSD 64GB	16GB eMMC
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640
LAN	10/100 Mbs, Realtek RTL8111F Lan chip	WIFI/802.11/b/g/n
Operating System	Windows 7/8/10, Embedded,WEPOS, Linux	Up to Android 8.1 (Android 7.1 for A63)
scanner	Bar-code scanner inbuilt	
<b>Connectivity</b>		
External port(J1900)	I/O	power button*1, 12V DC in jack*1
		LAN:RJ-45*1
		RS232*1
		USB *4
		Audio out*1

External port(RK3288)	I/O	power button*1, 12V DC in jack*1
		LAN:RJ-45*1
		HDMI*1
		USB *2
		SIM slot*1, SD card slot*1
		Audio out*1
External port(A63)	I/O	power button*1, 12V DC in jack*1
		LAN:RJ-45*1
		USB *4
		SD card slot*1
		Audio out*1
<b>Package</b>		
Weight	Net 1.5Kg Gross 3.0Kg	
Package with foam inside	360*290*180mm	
<b>Environment</b>		
Operating temperature	0 to 40 degrees centigrade	
Storage temperature	-10 to 60 degrees centigrade	
Working humidity	10%~80% No condensation	
Storage humidity	10%~90% No condensation	
<b>Accessories</b>		
Power adapter	110-240V/50-60HZ AC power input ,DC12V/5A output	
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available	
<b>Other</b>		
Compliance	FCC Class A/CE Mark/LVD/CCC	















