POS-T1N 4G rugged qr code android smart mobile pos pos payment terminal for restaurant

(Model: POS-T1N)

The T1N smart android POS terminal can meet kinds of needs, like NFC cards pay, QR Code pay, top up, info management, data transmission, receipt/ticket/lottery/coupon printing. It was widely used in retail, hotel, restaurant, hospital, government, transportation, logistics, parking etc.

Features:

Android 7.0 OS;

NFC Card Reader;

4G / 3G / 2G / Wi-Fi / Bluetooth / GPS;

5.0 Inch Touch Screen;

Rear Camera for QR Code Payment;

58*40mm Thermal Printer.

| The Specification | |
|------------------------------|---|
| Operation System | Android 7.0 |
| Processor | Application CPU: ARM Cortex A53 1.3 GHz, 64 bite Quad core Processor + Security CPU |
| Memory | RAM[]1GB(EMCP); Flash[]8GB(EMCP)[] |
| Display | 5 inch IPS color LCD screen (1280*720); Capacitive multi-touch with signature functionality; |
| Button | Physical Button: 1* Power on/off ,1*Home and 1 * Function Virtual Button: 1* Menu ,1*Home and 1 * Return |
| NFC Card Reader | Support Mifare card, type A/B card and compliance with ISO14443 A/ B |
| LED Indicator | Four indicator lights: Blue, Yellow, Green, Red |
| Thermal Printer | Print speed: 80mm/s; Paper roll: 58*40mm |
| Camera | 2 MP rear-facing with flash light; |
| Audio | 1*speakers,1*beeper,1* microphones |
| Communication | Bluetooth□ Support 4.2 HS low energy; Wi-Fi: Support 802.11 a/b/g/n; Mobile Network: 2G: GSM/EDGE/GPRS 850 900 1800 1900; 3G: CDMA/WCDMA; 4G: LTE |
| Location | Support GPS, GLONASS,BEIDOU |
| Device Port | 1 * Micro USB OTG |
| Card Slot | 1*SIM+1*PASM+1*TF or 2 *SIM+1*TF |
| Battery | 4000mAh Li-ion; Standby: >3 days; supports more than 500 transactions |
| Adapter | Input: 100-240V, 50Hz/60Hz; Output: 5V/1A; Charging time: < 3 hours |
| Environment Applicability | Working Temperature: -10°C□55°C Working Humidity: 5%□90% Storage Temperature: -20°C□70°C Storage Humidity: 5%□93%(40°C) |

| Dimension | 193*80*54.5mm |
|-----------|------------------------|
| Weight | 425g (include battery) |



















































Relevant documents:

POS-T1N SPEC