# Touch Bluetooth WIFI Portable Mobile Pos Terminal NFC Android Handheld Pos machine

(Model: POS-T1N)

The T1N smart android POS terminal can meet kinds of needs, like NFC cards pay, QR Code pay, top up, info management, data transmission, receipt/ticket/lottery/coupon printing. It was widely used in retail, hotel, restaurant, hospital, government, transportation, logistics, parking etc.

#### Features:

Android 7.0 OS;

NFC Card Reader;

4G / 3G / 2G / Wi-Fi / Bluetooth / GPS;

5.0 Inch Touch Screen;

Rear Camera for QR Code Payment;

58\*40mm Thermal Printer.

| The Specification            |   |
|------------------------------|---|
| Operation<br>System          | Android 7.0   |
| Processor                    | Application CPU: ARM Cortex A53 1.3 GHz, 64 bite Quad core Processor + Security CPU   |
| Memory                       | RAM[]1GB(EMCP); Flash[]8GB(EMCP)[]  |
| Display                      | 5 inch IPS color LCD screen (1280*720);<br>Capacitive multi-touch with signature functionality;   |
| Button                       | Physical Button: 1* Power on/off ,1*Home and 1 * Function<br>Virtual Button: 1* Menu ,1*Home and 1 * Return                                       |
| NFC Card<br>Reader           | Support Mifare card, type A/B card and compliance with ISO14443 A/ B  |
| LED Indicator                | Four indicator lights: Blue, Yellow, Green, Red   |
| Thermal Printer              | Print speed: 80mm/s; Paper roll: 58*40mm  |
| Camera                       | 2 MP rear-facing with flash light;  |
| Audio                        | 1*speakers,1*beeper,1* microphones  |
| Communication                | Bluetooth□ Support 4.2 HS low energy; Wi-Fi: Support 802.11 a/b/g/n; Mobile Network: 2G: GSM/EDGE/GPRS 850 900 1800 1900; 3G: CDMA/WCDMA; 4G: LTE |
| Location                     | Support GPS, GLONASS,BEIDOU   |
| Device Port                  | 1 * Micro USB OTG   |
| Card Slot                    | 1*SIM+1*PASM+1*TF or 2 *SIM+1*TF  |
| Battery                      | 4000mAh Li-ion; Standby: >3 days; supports more than 500 transactions   |
| Adapter                      | Input: 100-240V, 50Hz/60Hz; Output: 5V/1A; Charging time: < 3 hours   |
| Environment<br>Applicability | Working Temperature: -10°C□55°C<br>Working Humidity: 5%□90%<br>Storage Temperature: -20°C□70°C<br>Storage Humidity: 5%□93%(40°C)                  |

| Dimension | 193*80*54.5mm          |
|-----------|------------------------|
| Weight    | 425g (include battery) |



















































#### Relevant documents:

POS-T1N SPEC