

8" Android POS Terminal with Thermal Label and Receipt Printer

(Model: POS-T8)

Feature:



This android smart integrates printer,NFC,Infrared scanner (optional), Built in 8 inch IPS capacitive screen, multiple point touch, super long standby time with 7.6V 3200 mAh(Equal 3.8V 6400mAh) big capacity battery,thermal and label printer,with LTE 4G/3G/2G network, WiFi, BT, GPS functions, fine workmanship and high quality device is the best choice in the market.

The device with Android 12 system,opened Android system allows users to develop upper-layer applications simply and efficiently.

Scope of service: Applicable to chain supermarkets, catering, parking systems, prepaid card recharge, convenience stores, clothing stores, storefronts, bakeries, cashiers, payment, purchase, sale and storage, etc. Enterprise management functions.

Specification:

| | |
|----|------------|
| OS | Android 12 |
|----|------------|

| | |
|--------------------|---|
| MDM | Within MDM control system (for optional) |
| Main Chip | 8 Core SC9863 |
| Frequency | 1.6GHz |
| RAM | 3GB |
| ROM | 16GB |
| LCD Screen | 8 inch+ Digital display |
| Display Resolution | 800*1280 IPS |
| Back light | LED |
| Touch Screen | Capacities Five-Point Touch |
| SIM card bands | Europe Brand GSM B2/3/5/8 WCDMA B1/2/5/8 LTE B1/2/3/5/7/8/20/40 American Brand GSM: B2/3/5 WCDMA: B2/4/5 LTE: B2/3/4/5/7/17/40 |
| Voice call | Support |
| Data | Support |
| WIFI Module | 802.11 b/g/n, support 2.4G |
| Bluetooth | BT4.2 |
| GPS | GPS |
| USB | USB 2.0(OTG) |
| Fingerprint module | Optional |
| Speaker | 8Ω/1W*1 |
| Microphone | Mic*1 |
| Slot | SIM x2; Type-Cx1 |
| Physical button | Power, Vol+/-, Reset |
| Weight | 500g (one package box including product is 750g) |
| Package | 257*135.5*119.5mm |
| 8 in1 carton | 494*270*288mm |
| Battery | 7.6V 3200mAh Pure Cobalt Lithium Battery |
| Power adapter | 5V/2A |
| Scanner | Support 2D scanner (optional) |
| NFC | ISO/IEC 14443 Type A/B, Mifare 1 |

| | |
|----------------------|---|
| Printer | Paper width: 58mm□80mm optional |
| | Max. paper roll diameter: 40mm |
| | Support Thermal and label printing |
| Standard Accessories | 1pcs power adaptor, 1pcs User Manual, 1pcs USB cable, 1pcs roll paper |
| Temperature | Storage temperature: -10°C-60°C Working Temperature: 0°C-40°C |
| Certificate | CE |



















