POS-T8 made in china EMV 3G android handheld pos device with printer MSR NFC

Android 4.4 operation system. Adopts Qualcomm quad-core 1.26Hz processor. 4.0 inches IPS capacitive touch screen. Safety and reliable design Passed Unionpay Pbc 1.Et 2. passed PIN input safety certification. Unionpay adjrect connect POS network access. Support Printing Receipt and Braccode reading Supports magnetic stripe card, IC card, contactless card.	
System Parameters	
CPU	Qualcomm quad-core 1.2GHz
OS	Android 4.4
RAM/ROM	ROM 4GB eMMC; RAM 512MB/1GB DDR2;
	support external micro SD card, 32 GB at most
Display	4.0 inch capacitive, multi touch; 480*800, IPS display
Keypad	3 Touch System Keys, 15 physical keys (include Power key, Custom key, POS Cipher key a nd Command key)
Battery	Lithium polymer battery, 4000mAh
Functional Configuration	
Camera	Rear Camera 5M AF (support flashlight), Front Camera 0.3M wide angle
Printer	Built-in 2 inches thermal printer
Navigation	Built-in GPS, support AGPS
Indicator Light	System indicator light, POS indicator light
Audios	Built-in speaker, buzzer, microphone, vibrator
Sensors	Gravity sensor
POS	In a second
Sound Wave Payment	Support
Magnetic Strip Card	Triple track MSR, bi-directional swiping ISO7811, 7812
IC Card	1 Solt, Support 1.8V/3V/5V, ISO7816, PBOC and EMV
Contactless card	13.56MHz, ISO/IEC 14443 Type A/B, qPBOC
SAM Card	1 SAM Solt, ISO7816
Cipher Keyboard	Built-in keypad
Network Parameters	Part III Nel Part
Network Type	WCDMA/GSM
Network Spectrum	WCDMA 2100MHz
network Specialis	GSM/GPRS/EDGE 850/900/1800/1900MHz
WLAN	802.11 a/b/g/n Built-in Antenna
Voice/Data Service	Support Support
WPAN	Bluetooth V4.0 + EDR
External Interface	Indiction 1 44.0 1 EDR
USB Interface	Micro USB2.0, support USB OTG
Charger Jack	DC IACK
Power Supply Jack	Pogo Pin, 5V500mA
Communication	USB. RS232
Physical Parameters	036, 63232
Dimensions	205mm H * 82mm/67mm W * 33mm D
	500q (battery included)
Weight Operating Town	-20°C ~ 60°C
Operating Temp	-20°C ~ 60°C
Storage Temp	
Humidity	10%~90% RH non-condensing
Drop Test	1.0-meter drop protection
Roller Drop Test	500 times
ESD protection	±8KV contact discharge; ±15KV air discharge
Development Environment	I
System Environment	Android 4.4/SP-UI
Development Environment	SDK
Management Software	PC management suite/MDM