

8" Android POS Terminal with Thermal Label and Receipt Printer

(Model: POS-T8&T8R)

Feature:



T8&T8R is a Android POS with 80mm or 58mm Receipt and label printer, it has good ID design and CMF. Build in 8 inch touch screen, android operating system and Dual SIM 4G LTE, WiFi, Bluetooth, GPS communication.

It has an advanced main SOC 8 core 1.6GHz or RK3562 CPU for option and large memory capacity 3GB+16GB or 4GB+64GB, make sure each application runs smoothly.

It build in super long standby& removable battery 3.8V/6400mAh which 100% Pure Cobalt Lithium and Recharge 400Cycle ≥80% to keep it runs 1-2years w/o any trouble.

Automatic Fixed 2D bar code scanning model which can One key scan make you scanning easy and faster.

Specification:

Model	POS-T8	POS-T8R
Operating System	Android 12.0	Android 13.0
CPU	8-Core SC9863, 1.6GHz	4 Core RK3562, 2.0GHz
RAM	3GB (4G Optional)	4GB (2G Optional)
Flash	16GB (64G Optional)	64GB (16G Optional)
LCD Screen	8-inch	8-inch
Display Resolution	800*1280 IPS	800*1280 IPS
Second Small LCD	2.4-inch LCD (Optional)	2.4-inch LCD (Optional)
Touch Screen	10-Point capacitive touch	10-Point capacitive touch
Fingerprint Collection Module	NA	FBI/STQC (Optional)
SIM Card Bands	Europe Brand: GSM: B2/3/5/8 WCDMA: B1/2/5/8 LTE: B1/2/3/5/7/8/20/40 American Brand: GSM: B2/3/5 WCDMA: B2/4/5 LTE: B2/3/4/5/7/17/40	B1/B3/B5/B7/B8/B20/B28 B2/B3/B5/B8
WIFI Module	2.4G, 802.11 b/g/n	2.4G/5G, 802.11 ac/b/g/n
Bluetooth	4.2	5.2
GPS	Support	N/A
USB	Type-C USB2.0□OTG□	Type-C USB2.0 (OTG)
Scanner	1D/2D Bar code scanner	1D/2D Bar code scanner
Speaker	8ohm/1w*1	8ohm/1w*1
Slot	SIM*2, Type-C*1	RJ11*1, RJ12*1, RJ45*1 USB A*2, DC*1(Charging) SIM*1, TF*1, Type-C*1(OTG)
Physical Button	Power, Vol+/-, Reset	Power, Vol+/-, Reset
Battery	Lithium battery	Lithium battery
Battery Capacity	3.8V 6400mAh(7.6V 3200mAh) Removable 100% Pure Cobalt Lithium Battery 400Cycle≥80%	3.8V 6400mAh(7.6V 3200mAh) Removable 100% Pure Cobalt Lithium Battery 400Cycle≥80%
Power Adapter	5V/2A	12V/2A Fast charging
NFC	ISO/IEC 14443 Type A/B, Mifare1	ISO/IEC 14443 Type A/B, Mifare1

Printer	Paper width: 80mm/58mm	Paper width: 80mm/58mm
	Max. paper roll diameter: 40mm	Max. paper roll diameter:40mm
Standard Accessories	Power adaptor, User manual, USB cable, 58mm or 80mm roller thermal paper	Power adaptor, User manual, USB cable, 58mm or 80mm roller thermal paper
Temperature	Storage temperature: -10°C-60°C Working temperature: 0°C-40°C	Storage temperature: -10°C-60°C Working temperature: 0°C-40°C



















