

# **15"Touch Screen All-in-one POS System/Machine/Cash Register for Retail**

## **(Model:POS8829)**

### **Features:**

15 Inch All-in-one Touch Screen POS Machine in China  
15 Inch All-in-one Touch Screen POS Machine  
Fashion wine red appearance beautiful and streamlined design  
Humanized design can desktop or wall-mounted  
Inter processor 1037U dual core 1.8GHz  
1024x768 high resolution  
Magnetic card reader, LCD customer display,LED8 display, wifi optional  
SATA2.5 320GB or 500GB or SSD32GB  
15 inch TFT LCD and 5 wire resistive touch screen  
PS/2x2, serial3 DB9 malex3, parallel USB2.0x6, Parallel DB25 port, VGA, LAN port;  
HDMI, RJ11 for cash drawer optional

### **Applications:**

- Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

### **Specifications:**

Model	POS8829
Optional Color	Black/ Wine red
Optional Peripherals	ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI
Main Board	Intel Chipset
CPU	1037U dual core 1.8G
Chipset	1037U + ICH8 Chipset
Memory Support	DDRIII 1066/1333*1 2GB(up to 4GB)
Hard Driver	SATA 2.5 320GB or 500GB or SSD32GB
LCD panel Size	15 inch TFT LCD
Brightness	350cd/m <sup>2</sup>
Resolution	1024*768(max)

Touch Screen	5 wire resistive touch screen
View Angle	Horizon: 150; Vertical: 140
I/O port	1* power button
	PS2 mouse*1; PS2 keyboard*1
	Serial*3 DB9 male
	Parallel * 1, DB25 Parallel port
	VGA(15Pin D-sub)*1
	LAN: RJ-45*1    HDMI * 1    RJ*11 for cash drawer optional
	USB(2.0) * 6
	Audio out*12*Internal Speaker(option), MIC IN*1
Operating temperature	0 to 40 degree centigrade
Storage temperature	-20 to 60 degree centigrade
Power Consumption	35W(max)
Compliance	FCC Class A/CE Mark/LVD/CCC
Packing dimension/ Weight	440*270*425mm / 8 KGS
Operating System	Windows XP Professional Embedded (WEPOS, Linux compatible)
Power adapter	110-240V/50-60HZ AC power Input, DC12/5A output