

## 15 Inch All-In-One Touch POS Terminal

(Model No.: POS8829T)

### Features:

- Good-looking design is suitable for many POS field
- Low power-consumption solution guarantees its stable quality and safety
- LED/LCD customer display optional
- MSR optional
- Wifi optional

### Applications:

- Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

### Specifications:

|  |   |
|--|---|
| Model  | POS8829T  |
| Optional Color   | Black/ Wine red   |
| Optional Peripherals   | ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI |
| Main Board   | Intel Chipset   |
| CPU  | Celeron J1900 Quad core 2.0 GHZ   |
| Memory Support   | DDRIII 1066/1333*1 2GB(up to 4GB)                                       |
| Hard Disk  | SSD32GB   |
| LCD panel Size   | 15 inch TFT LCD   |
| Vice screen <input type="checkbox"/> Optional <input type="checkbox"/> | 12inch,1024*768   |
| Brightness   | 350cd/m <sup>2</sup>  |
| Resolution   | 1024*768(max)   |
| Touch Screen   | 5 wire resistive touch screen   |
| View Angle   | Horizon: 150; Vertical: 140   |
| I/O port   | 1* power button   |
|  | Serial*2 DB9 male   |
|  | VGA(15Pin D-sub)*1  |
|  | LAN: RJ-45*1  |
|  | USB(2.0) * 6  |
|  | Audio out*12*Internal Speaker(option), MIC IN*1                         |
| Operating temperature  | 0 to 40 degree centigrade   |
| Storage temperature  | -20 to 60 degree centigrade   |

|                           |  |
|---------------------------|--|
| Power Consumption         | 35W(max)   |
| Compliance                | FCC Class A/CE Mark/LVD/CCC                                |
| Packing dimension/ Weight | 440*270*425mm / 8 KGS                                      |
| Operating System          | Windows XP Professional Embedded (WEPOS, Linux compatible) |
| Power adapter             | 110-240V/50-60HZ AC power Input, DC12/5A output            |

**Power adaptor for option:**





POS8829





POS8829





POS8829





POS8829

