Shenzhen computer pos electronic cash register machine

(Model: POS -15T01-W / A)





feature:

Sleek minimalist design

15.6" 1366 * 768 resolution slim screen

360 degree screen rotation angle

Support for Windows or Android systems

Ten-point capacitive touch screen

Optional secondary screen 15.6 inches or 11.6 inches

MSR, customer display options

Modular design, easy to assemble, disassemble, replace and repair

application:

Dining: hotels, restaurants, fast food restaurants, coffee shops, bakeries and cake shops

Retailers: commercial streets, boutiques, department stores, cosmetics stores and premium barbershops

Entertainment: sauna, spa, night club, theme park, casino and lottery point of sale

Business: information management terminal for parking lots, hotels, airlines, subways, stations and terminals

Product specifications:

| model | POS -15T01-W / A (W for Windows, A for Android) |
|--------------------------|--|
| Motherboard 1 | Quad-core 1.99 GHz J1900N for Windows version |
| Motherboard 2 | Quad-core 1.8GHz RK3288 for Android |
| Windows operating system | Windows 7 Ultimate demo without license |
| Android operating system | Android 6.0 |
| Windows RAM | 4GB standard 8GB or higher optional |
| Android RAM | 2GB |
| Windows memory | 64GB SSD standard, , 128GB or higher optional |
| Android memory | 8GB eMMC, support 32GB TF card expansion |
| screen size | 15.6-inch home screen |
| Auxiliary screen | 15.6 inches or 11.6 inches |
| Customer show | VFD or LCD |
| Resolution | 1366 * 768 |
| touch screen | Ten-point capacitive touch screen |
| brightness | Brightness 350cd / meter ² |
| Perspective | Horizon: 150; vertical: 140 |
| J1900 I / O port | VGA * 1, USB * 5, RS232 * 1, DC input * 1 RJ45 (Ethernet port)* 1, audio output* 1 |
| RK3288 I / O port | USB * 5, RS232 * 2, DC input * 1, RJ11 (cash drawer port) * 1 RJ45 (Ethernet port)* 1, audio output* 1, MIC * 1 |
| Operating temperature | 0 to 40 degrees Celsius |
| Storage temperature | -20 to 60 degrees Celsius |
| Power Adapter | 110-240V / 50-60HZ AC power input, DC12 / 5A output |

image:



POS-15T01











POS-15T01









Involvedd PRODUCTS:

Https:// starts with WWW. ocom inc.com/products/All-in-one- POS -Machine.htm